

Metal NEMA 4X, Pushbutton 2 position, 1NO Complete device
Momentary Flush, green Non-Illuminated UL file E22655 in Vol. 6 (7)
Sec. 13 (2)



Figure similar

Enclosure	
Number of command points	1
Delivery state	
• as a kit	No
Actuator	
Design of the operating mechanism	Pushbutton
Material of the actuating element	plastic
Number of contact modules	1
Type of unlocking device	without
Number of switching positions	2
Front ring	
Product component front ring	Yes
Design of the front ring	standard
Material of the front ring	metal
Color of the front ring	black
General technical data	

Product function	
• positive opening	No
Product component	
• Light source	No
Insulation voltage	
• rated value	600 V
Surge voltage resistance rated value	4 kV
Protection class IP	IP66
• of the terminal	IP20
Thermal current	10 A
Operating voltage	
• at AC	
— at 60 Hz rated value	5 ... 600 V
• at DC rated value	5 ... 600 V

Auxiliary circuit	
Number of NC contacts for auxiliary contacts	0
Number of NO contacts for auxiliary contacts	1
Operating current at AC-15	
• at 110 V rated value	60 A
• at 230 V rated value	30 A
• at 400 V rated value	15 A
• at 500 V rated value	12 A

Connections/ Terminals	
Type of electrical connection	screw-type terminals
Tightening torque of the screws in the bracket	20 N·m
Tightening torque [lbf·in]	
• with screw-type terminals	8 lbf·in

Ambient conditions	
Ambient temperature	
• during operation	-35 ... +70 °C
• during storage	-40 ... +85 °C

Installation/ mounting/ dimensions	
Shape of the installation opening	round
Mounting height	21 mm
Installation width	48 mm
Installation depth	35 mm

Certificates/ approvals	
--------------------------------	--

Further information	
Information- and Downloadcenter (Catalogs, Brochures,...)	
www.siemens.com/sirius/catalogs	

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52PX8A3K>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52PX8A3K>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52PX8A3K>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52PX8A3K&lang=en

last modified:

10/30/2019