

Data sheet for SIMOTICS S-1FK7



Figure similar

MLFB-Ordering data

1FK7034-2AK71-1QG0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data		Physical constants	
Rated speed	6000 rpm	Torque constant	0.84 Nm/A
Number of poles	6	Voltage constant at 20° C	55.0 V/1000*min ⁻¹
Rated torque (100 K)	1.0 Nm	Winding resistance at 20° C	4.46 Ω
Rated current	1.3 A	Rotating field inductance	17.2 mH
Static torque (60 K)	1.35 Nm	Electrical time constant	3.85 ms
Static torque (100 K)	1.6 Nm	Mechanical time constant	1.71 ms
Stall current (60 K)	1.6 A	Thermal time constant	30 min
Stall current (100 K)	1.9 A	Shaft torsional stiffness	5300 Nm/rad
Rotor moment of inertia	0.900 kgcm ²	Net weight of the motor	3.5 kg
Efficiency	88.0 %		

Mechanical data			
Motor type	Compact	Electrical connectors	Connectors for signals and power rotatable
Shaft height	36	Color of the housing	Standard painting (Anthracite RAL 7016)
Cooling	Natural cooling	Holding brake	without holding brake
Radial runout tolerance	0.035 mm	Shaft extension	Plain shaft
Concentricity tolerance	0.08 mm	Encoder system	Encoder AS20DQI: absolute encoder single-turn 20 bits
Axial runout tolerance	0.08 mm		
Vibration severity grade	Grade A		
Connector size	1		
Degree of protection	IP64		
Design acc. to Code I	IM B5 (IM V1, IM V3)		
Temperature monitoring	KTY84 temperature sensor in the stator winding		



Figure similar

MLFB-Ordering data

1FK7034-2AK71-1QG0

Optimum operating point		Recommended Motor Module	
Optimum speed	6000 rpm	Rated inverter current	3 A
Optimum power	0.6 kW	Maximum inverter current	6 A
Limiting data		Maximum torque	4.95 Nm
		Max. permissible speed (mech.)	10000 rpm