



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : **1PH8288-1HC40-2BW2-Z**
G00

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Δ	ALM 400V	310.0	3,701.0	560.0	370	27.2	800	6,450	970.0	3,300	3,701.0	560	0.945	0.910	164.0
	BLM/SLM 400V	272.0	3,711.0	570.0	325	23.9	700	6,450	970.0	3,300	3,711.0	570	0.939	0.910	161.0
	ALM/BLM/SLM 480V	385.0	3,677.0	560.0	460	33.9	1,000	6,450	970.0	3,300	3,677.0	560	0.953	0.910	164.0

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	280
Cooling	Open circuit cooling NDE-> DE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP23
Design acc. to Code I	IM B3 (IM V6)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft end	Feather key with half key balancing
Encoder system	Incremental encoder HTL 1024 S/R, max. encoder speed = 9000 rpm

Physical constants

Thermal time constant	22 min
Moment of inertia	63,000 kgcm ²
Weight (approx.)	1,650 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	1XB7700-P02

Cooling data and sound pressure level

Airflow, min.	0.52 m ³ /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	74 dB ¹⁾
Air discharge	radial
Pressure drop	600 Pa

External fan

Max. power consumption

3 AC 380 ... 480 V (-5% / +10%)
50/60 Hz ±10% 0.75 ... 0.90 A

Special design

G00 Separately-driven fan NDE left, air intake NDE

¹⁾ at a rated frequency of 2 kHz and a speed range of up to 2800 rpm