

## Data sheet for SIMOTICS S-1FT7

MLFB-Ordering data

1FT7082-1AF71-1BH1



Figure similar

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

Engineering data		Mechanical data	
Rated speed	3000 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	10	Design of the motor type	Compact core type
Rated torque (100 K)	10.3 Nm	Shaft height	80 mm
Rated current	6.6 A	Cooling	Natural cooling
Static torque (60 K)	10.60 Nm	Radial runout tolerance	N
Static torque (100 K)	13.0 Nm	Vibration severity grade	Grade A
Stall current (60 K)	6.1 A	Degree of protection	IP65
Stall current (100 K)	7.6 A	Design acc. to Code I	IM B5 (compatible with 1FT6)
Rotor moment of inertia	0.0041900 kgm <sup>2</sup>	Temperature monitoring	Pt1000 temperature sensor
Efficiency	93.0 %	Color of the housing	
Physical constants		Holding brake version	Permanent-magnet brake
Torque constant	1.71 Nm/A	Shaft end type	Plain shaft
Voltage constant at 20° C	108.0 V/1000*min <sup>-1</sup>	Sensor design	Encoder AS24DQI: Absolut encoder Singleturn 24 bit - with signal connection RJ45
Winding resistance at 20° C	0.59 Ω	Electrical connectors	Connector turnable
Rotating field inductance	9.3 mH	Connector size	1
Electrical time constant	15.80 ms		
Mechanical time constant	1.60 ms		
Thermal time constant	40 min		
Shaft torsional stiffness	75700 Nm/rad		
Net weight of the motor	18.3 kg		

## Data sheet for SIMOTICS S-1FT7

MLFB-Ordering data

1FT7082-1AF71-1BH1



Figure similar

Optimum operating point		Recommended Motor Module	
Optimum speed	3000 rpm	Rated inverter current	9 A
Optimum power	3.2 kW	Maximum inverter current	18 A

  

Limiting data	
Max. permissible speed (mech.)	8000 rpm
Max. permissible speed (inverter)	5400 rpm
Maximum torque	52.0 Nm
Maximum current	39.0 A