

## Data sheet for SIMOTICS S-1FK7

MLFB-Ordering data

1FK7101-2AF71-1BG0-Z  
L13



Figure similar

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

| Engineering data            |                               | Mechanical data          |   |
|-----------------------------|-------------------------------|--------------------------|---|
| Rated speed (100 K)         | 3000 rpm                      | Motor type               | Permanent-magnet synchronous motor                    |
| Number of poles             | 8                             | Motor type               | Compact   |
| Rated torque (100 K)        | 15.5 Nm                       | Shaft height             | 100   |
| Rated current               | 11.6 A                        | Cooling                  | Natural cooling                                       |
| Static torque (60 K)        | 22.50 Nm                      | Radial runout tolerance  | 0.050 mm  |
| Static torque (100 K)       | 27.0 Nm                       | Concentricity tolerance  | 0.10 mm   |
| Stall current (60 K)        | 15.20 A                       | Axial runout tolerance   | 0.10 mm   |
| Stall current (100 K)       | 18.80 A                       | Vibration severity grade | Grade A   |
| Moment of inertia           | 79.000 kgcm <sup>2</sup>      | Connector size           | 1.5   |
| Efficiency                  | 93.0 %                        | Degree of protection     | IP64  |
| <b>Physical constants</b>   |                               | Design acc. to Code I    | IM B5 (IM V1, IM V3)                                  |
|                             |                               | Temperature monitoring   | Pt1000 temperature sensor                             |
| Torque constant             | 1.44 Nm/A                     | Electrical connectors    | Connectors for signals and power rotatable            |
| Voltage constant at 20° C   | 92.5 V/1000*min <sup>-1</sup> | Color of the housing     | Standard (Anthracite RAL 7016)                        |
| Winding resistance at 20° C | 0.14 Ω                        | Holding brake            | without holding brake                                 |
| Rotating field inductance   | 3.5 mH                        | Shaft extension          | Plain shaft   |
| Electrical time constant    | 25.00 ms                      | Encoder system           | Encoder AS24DQI: absolute encoder single-turn 24 bits |
| Mechanical time constant    | 1.62 ms                       |                          |   |
| Thermal time constant       | 60 min                        |                          |   |
| Shaft torsional stiffness   | 164000 Nm/rad                 |                          |   |
| Net weight of the motor     | 23.0 kg                       |                          |   |



Figure similar

**MLFB-Ordering data**

**1FK7101-2AF71-1BG0-Z  
L13**

### Optimum operating point

|               |          |
|---------------|----------|
| Optimum speed | 3000 rpm |
| Optimum power | 4.8 kW   |

### Limiting data

|                                   |          |
|-----------------------------------|----------|
| Max. permissible speed (mech.)    | 5000 rpm |
| Max. permissible speed (inverter) | 5000 rpm |
| Maximum torque                    | 80.0 Nm  |
| Maximum current                   | 63.0 A   |

### Recommended Motor Module

|                          |          |
|--------------------------|----------|
| Rated inverter current   | 18 A     |
| Maximum inverter current | 54 A     |
| Maximum torque           | 72.00 Nm |

### Special design

L13 External ground connection