

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8137-1SS00-0LA1



Figure similar

Client order no. :

Item no. :

Order no. :

Consignment no. :

Offer no. :

Project :

Remarks :

Engineering data

		P_N [kW]	M_N [Nm]	I_N [A]	U_N [V]	f_N [Hz]	n_N [rpm]	M_{max} [Nm]	I_{max} [A]	n_{max} [rpm]	M_0 [Nm]	I_0 [A]	η	$\cos \varphi$	μ [A]
Y	ALM 400V	29.0	138.0	56.0	398	68.0	2,000	320	130.0	10,000.0	185.0	68	0.931	0.85	22.7
	BLM/SLM 400V	22.0	140.0	56.0	308	51.3	1,500	320	130.0	10,000.0	185.0	68	0.902	0.84	24.2
	ALM/BLM/SLM 480V	36.0	138.0	50.0	460	84.9	2,500	320	130.0	10,000.0	185.0	68	0.951	0.89	17.4
Δ	ALM 400V	27.5	53.0	56.0	425	167.5	5,000	160	160.0	10,000.0	105.0	87	0.919	0.83	22.5
	BLM/SLM 400V	22.0	53.0	55.0	383	134.0	4,000	160	160.0	10,000.0	105.0	87	0.907	0.76	27.6
	ALM/BLM/SLM 480V	33.0	53.0	55.0	460	201.0	6,000	160	160.0	10,000.0	105.0	87	0.942	0.87	20.0

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	132
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	SPECIAL/B
Shaft and flange accuracy	SPECIAL
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM V5, IM V6)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Performance
Shaft extension	Plain shaft
Encoder system	Incremental encoder 19 bit without commutation position (encoder IN19DQ)

Physical constants

Thermal time constant	30 min
Moment of inertia	0.109 kgm ²
Weight (approx.)	141 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	gk846

Cooling data and sound pressure level

Airflow, min.	0.09 m ³ /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	70 dB ¹⁾
Air discharge	axial
Pressure drop	140 Pa

¹⁾ at a rated frequency of 4 kHz and a speed range of up to 5000 rpm