

Selector switch, metal Maintained, long lever left, 1NC + 1NO right position, A Cam 2 position Complete device white insert Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)

### Enclosure

Number of command points	1
Delivery state	No
<ul style="list-style-type: none"> <li>as a kit</li> </ul>	No

### Actuator

Material of the actuating element	plastic
Number of contact modules	2
Type of unlocking device	rotate-to-unlatch mechanism
Number of switching positions	2

### Front ring

Product component front ring	Yes
Design of the front ring	standard
Material of the front ring	metal

### General technical data

Product function	Yes
<ul style="list-style-type: none"> <li>positive opening</li> </ul>	Yes
Product component	No
<ul style="list-style-type: none"> <li>Light source</li> </ul>	No
Insulation voltage	600 V
<ul style="list-style-type: none"> <li>rated value</li> </ul>	600 V
Protection class IP	IP66
<ul style="list-style-type: none"> <li>of the terminal</li> </ul>	IP20
Operating frequency maximum	600 1/h
Thermal current	10 A

### Auxiliary circuit

Number of NC contacts for auxiliary contacts	1
Number of NO contacts for auxiliary contacts	1
Operating current at AC-15	60 A
<ul style="list-style-type: none"> <li>at 110 V rated value</li> </ul>	60 A
<ul style="list-style-type: none"> <li>at 500 V rated value</li> </ul>	12 A

### Connections/ Terminals

Type of electrical connection	screw-type terminals
Tightening torque of the screws in the bracket	20 N·m

<b>Tightening torque [lbf·in]</b>	
<ul style="list-style-type: none"> <li>with screw-type terminals</li> </ul>	8 lbf·in

### Ambient conditions

<b>Ambient temperature</b>	
<ul style="list-style-type: none"> <li>during operation</li> </ul>	-35 ... +70 °C
<ul style="list-style-type: none"> <li>during storage</li> </ul>	-40 ... +85 °C

### Installation/ mounting/ dimensions

<b>Shape of the installation opening</b>	round
--	-------

### Certificates/ approvals

### Further information

- Information- and Downloadcenter (Catalogs, Brochures,...)**  
[www.siemens.com/sirius/catalogs](http://www.siemens.com/sirius/catalogs)
- Industry Mall (Online ordering system)**  
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SB2AABJ0K0>
- Cax online generator**  
<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SB2AABJ0K0>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**  
<https://support.industry.siemens.com/cs/ww/en/ps/US2:52SB2AABJ0K0>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**  
[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=US2:52SB2AABJ0K0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SB2AABJ0K0&lang=en)

last modified: 11/15/2019