

## MOTION CONNECT 700

MLFB-Ordering data

6FX7002-5EB11-1AK5



Figure similar

Client order no. / :

Order no. / :

Offer no. / :

Remarks / :

Item no. / :

Consignment no. / :

Project / :

### General data :

Components :	power cable preassembled
Cable / installation:	4X2,5+(4X0,5)C
Cable outer diameter:	15.2 mm
Weight:	3.310 kg
Length:	9.5 m
Degree of protection:	IP67
Connector size:	1.0

### Mechanical Data :

Maximum / fixed installation:	50.0 N/mm <sup>2</sup>
Maximum / moved:	20.0 N/mm <sup>2</sup>
Bending radius / min. / fixed installation:	60.8 mm
Bending radius / min. / moved:	110.0 mm
Stress / torsion:	30.0 %/m
Bends / 1.5 to 6 mm <sup>2</sup> :	10000000
Bends / 10 to 50 mm <sup>2</sup> :	
Traversing velocity / 1.5 to 6 mm <sup>2</sup> :	200.0 m/min
Traversing velocity / 10 to 50 mm <sup>2</sup> :	200.0 m/min
Acceleration:	30.0 m/s <sup>2</sup>

### Licences :

Licence / VDE:	Yes
Licence / UL/CSA:	Yes

### Electrical Data DIN VDE 0472 :

Supply lines / VDE:	600.0 V
Supply lines / UL/CSA:	1000.0 V
Signal lines / VDE:	24.0 V
Signal lines / UL/CSA:	1000.0 V
Rated voltage Un / signal line:	30.0 V
Power cable / supply lines:	4 kV
Power cable / signal lines:	2 kV
Signal line:	500 V

### Chemical Data :

Insulation material:	CFC/halogen/silicone-free IEC 60754-1/ DIN VDE 0472-815
Resistance to oil:	EN 60811-2-1
Flame-retardant:	EN 60332-1-1 to 1-3
Outer shield / power cable:	PUR, HD22.10 S2 (VDE 0282, Part 10) DESINA color orange RAL 2003
Outer shield / signal line:	PUR, HD22.10 S2 (VDE 0282, Part 10) DESINA color green RAL 6018

### Operating Temperature :

Fixed installation / min.:	-50.0 °C
Fixed installation / max.:	80.0 °C
Moved / min.:	-20.0 °C
Moved / max.:	60.0 °C

### Special design :