

Data sheet for SIMOTICS S-1FK7

MLFB-Ordering data

1FK7062-2AC71-1PG2



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data		Mechanical data			
Rated speed (100 K)	2000 rpm	Motor type	Permanent-magnet synchronous motor		
Number of poles	8	Motor type	Compact		
Rated torque (100 K)	7.0 Nm	Shaft height	63		
Rated current	2.6 A	Cooling	Natural cooling		
Static torque (60 K)	7.10 Nm	Radial runout tolerance	0.040 mm		
Static torque (100 K)	8.5 Nm	Concentricity tolerance	0.10 mm		
Stall current (60 K)	2.45 A	Axial runout tolerance	0.10 mm		
Stall current (100 K)	3.00 A	Vibration severity grade	Grade A		
Moment of inertia	11.200 kgcm ²	Connector size	1		
Efficiency	90.0 %	Degree of protection	IP65 and DE flange IP67		
Physical constants		Design acc. to Code I	IM B5 (IM V1, IM V3)		
		Temperature monitoring	Pt1000 temperature sensor		
		Electrical connectors	Connectors for signals and power rotatable		
		Color of the housing	Standard (Anthracite RAL 7016)		
		Holding brake	without holding brake		
		Shaft extension	Plain shaft		
		Encoder system	Resolver R14DQ: resolver 14 bits (resolution 16384, internal 2-pole)		
		Torque constant	2.83 Nm/A		
		Voltage constant at 20° C	180.5 V/1000*min ⁻¹		
		Winding resistance at 20° C	3.59 Ω		
Rotating field inductance	45.5 mH				
Electrical time constant	12.70 ms				
Mechanical time constant	1.51 ms				
Thermal time constant	35 min				
Shaft torsional stiffness	37000 Nm/rad				
Net weight of the motor	9.1 kg				



Figure similar

MLFB-Ordering data

1FK7062-2AC71-1PG2

Optimum operating point		Recommended Motor Module	
Optimum speed	2000 rpm	Rated inverter current	3 A
Optimum power	1.3 kW	Maximum inverter current	9 A
Limiting data		Maximum torque	22.90 Nm
Max. permissible speed (mech.)	7200 rpm		
Max. permissible speed (inverter)	3200 rpm		
Maximum torque	26.0 Nm		
Maximum current	10.9 A		