

LED module, red for plug-in relay, PT and RT series, for DC 24 V with freewheeling diode



General technical data

Display version LED	Yes
Protection class IP	IP00
Design of the switching function positively driven	No
Reference code acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	E
Reference code acc. to DIN EN 81346-2	P
Reference code acc. to DIN EN 61346-2	P

Control circuit/ Control

Control supply voltage at DC	
• rated value	24 V
Product component Plug-in socket	No

Auxiliary circuit

Number of NC contacts for auxiliary contacts	0
Number of NO contacts for auxiliary contacts	0
Number of CO contacts	
• for auxiliary contacts	0

Main circuit

Type of voltage	DC
-----------------	----

Display

Display version	LED red
• as status display by LED	




Connections/ Terminals

Product function	No
• removable terminal	

Installation/ mounting/ dimensions

Mounting position	any
Width	15.5 mm

Certificates/ approvals

General Product Approval	Declaration of Conformity	other
 UL	 EG-Konf.	Miscellaneous Confirmation
 VDE		

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)
www.siemens.com/sirius/catalogs

Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=LZS:PTML0024>

Cax online generator
<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=LZS:PTML0024>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/LZS:PTML0024>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=LZS:PTML0024&lang=en

last modified: 11/20/2019