



Figure similar

## Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8226-1AL10-2EA1

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

		$P_N$ [kW]	$M_N$ [Nm]	$I_N$ [A]	$U_N$ [V]	$f_N$ [Hz]	$n_N$ [rpm]	$M_{max}$ [Nm]	$I_{max}$ [A]	$n_{max}$ [rpm]	$M_0$ [Nm]	$I_0$ [A]	$\eta$	$\cos \phi$	$I_{\mu}$ [A]
Y	ALM 400V	185.0	609.0	335.0	390	97.1	2,900	1,450	740.0	4,500	609.0	335	0.960	0.850	152.0
	BLM/SLM 400V	168.0	642.0	350.0	335	83.8	2,500	1,450	740.0	4,500	642.0	350	0.961	0.860	151.0
	ALM/BLM/SLM 480V	90.0	253.0	205.0	460	113.5	3,400	1,450	740.0	4,500	253.0	205	0.926	0.600	156.0

### Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	225
Cooling	Forced ventilation NDE -> DE
Vibration severity grade	A
Shaft and flange accuracy	N
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM B6, IM B7, IM B8, IM V6)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Increased cantilever forces
Shaft extension	Feather key with half key balancing
Encoder system	Without encoder

### Physical constants

Thermal time constant	52 min
Moment of inertia	19,300 kgcm <sup>2</sup>
Weight (approx.)	740 kg

### Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	1XB7700-P02

### Cooling data and sound pressure level

Airflow, min.	0.31 m <sup>3</sup> /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB <sup>1)</sup>
Air discharge	axial
Pressure drop	650 Pa

### External fan

#### Max. power consumption

1 AC 200 ... 277 V ( $\pm 10\%$ ) 50/60 Hz $\pm 10\%$	2.0 ... 2.3 A
---	---------------

<sup>1)</sup> at a rated frequency of 2 kHz and a speed range of up to 3500 rpm