

## Data sheet for SIMOTICS S-1FK7

No image available for this configuration.

MLFB-Ordering data

1FK7083-5AF71-1SA3

Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data	
Rated speed (100 K)	3000 rpm
Number of poles	8
Rated torque (100 K)	10.5 Nm
Rated current	7.4 A
Static torque (60 K)	13.30 Nm
Static torque (100 K)	16.0 Nm
Stall current (60 K)	8.60 A
Stall current (100 K)	10.40 A
Moment of inertia	27.300 kgcm <sup>2</sup>
Efficiency	93.0 %

Physical constants	
Torque constant	1.52 Nm/A
Voltage constant at 20° C	97.0 V/1000*min <sup>-1</sup>
Winding resistance at 20° C	0.40 Ω
Rotating field inductance	6.0 mH
Electrical time constant	15.50 ms
Mechanical time constant	1.41 ms
Thermal time constant	50 min
Shaft torsional stiffness	105000 Nm/rad
Net weight of the motor	14.0 kg

Mechanical data	
Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	80
Cooling	Natural cooling
Radial runout tolerance	0.050 mm
Concentricity tolerance	0.10 mm
Axial runout tolerance	0.10 mm
Vibration severity grade	Grade A
Connector size	1
Degree of protection	IP64
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	Standard (Anthracite RAL 7016)
Holding brake	without holding brake
Shaft extension	Feather key
Encoder system	Multi-pole resolver (number of pole pairs corresponds to number of pole pairs of the motor)

MLFB-Ordering data

1FK7083-5AF71-1SA3

Figure similar

## Optimum operating point

Optimum speed 3000 rpm

Optimum power 3.3 kW

## Limiting data

Max. permissible speed (mech.) 6000 rpm

Max. permissible speed (inverter) 5900 rpm

Maximum torque 50.0 Nm

Maximum current 37.0 A

## Recommended Motor Module

Rated inverter current 9 A

Maximum inverter current 18 A

Maximum torque 27.80 Nm