

SIMATIC IPC BX-56A (box PC); mainboard (chipset H610E); 2x Gigabit Ethernet (IE/PN) RJ45 4x USB 3.1 Gen. 2; 2x serial (COM); 2x DP; audio; 2x SIM, slots; 2x M.2 flex module slots onboard; watchdog, temperature/fan monitoring Core i3-13100TE, 35 W; 4C (4P+0E)/8T; 2.4(4.1) GHz; with 9-36 V DC, 220 W power supply 1 TB 2.5" SATA SSD 8 GB DDR5(1*8) without ECC without hardware extension no power supply unit cable Windows 10 Enterprise LTSC 2021, 64-bit, MUI, for Pentium, Core i3, Core i5 (without USB USB-Stick restore image; D&D) no expansion module no expansion module, no EM memory

General information	
Product type designation	BX-56A
Installation type/mounting	
Mounting	Wall mounting, book mounting, desk mounting, tower mounting
Design	Box PC, built-in unit
Supply voltage	
Type of supply voltage	400 W / 24 V / 19.2 - 28.8 VDC; 220 W / 12-24 V / 9 - 36 VDC
Rated value (DC)	24 V; 12...24 V DC on 220 W
Mains buffering	
<ul style="list-style-type: none"> Mains/voltage failure stored energy time 	20 ms
Processor	
Processor type	Core i5-13500E 14C (6P+8E)/20T, 2.4 (4.6) GHz, 24 MB cache; Core i3-13100TE 4C (4P+0E)/8T, 2.4 (4.1) GHz, 12 MB cache; Pentium G7400E 2C (2P+0E)/4T, 3.6 GHz, 6 MB cache
Chipset	Intel H610E
Graphic	
Graphics controller	Intel UHD Graphics 710 (Pentium); Intel UHD Graphics 730 (Core i3); Intel UHD Graphics 770 (Core i5)
Drives	
SSD	Yes; base module: 512 GB 2.5" SATA SSD; 1 TB 2.5" SATA SSD;
Memory	
Type of memory	DDR5-4800 SO-DIMM
Main memory	8 / 16 / 32 / 64 GB
Capacity of main memory, max.	64 Gbyte
Data areas and their retentivity	
Retentive data area (incl. timers, counters, flags), max.	512 kbyte; 128 KB can be stored in the buffer time; optional
Hardware configuration	
Slots	
<ul style="list-style-type: none"> free slots 	2 slots: 1x PCI Express (x16) gen 4 (16 lanes) and 1x PCI Express (x4) gen 3 (4 lanes)
Interfaces	
Number of industrial Ethernet interfaces	2; 2x Gigabit Ethernet (RJ45)
USB port	2x USB 3.2 GEN2 10G Type A, 2x USB 3.2 GEN1 5G Type A
Connection for keyboard/mouse	USB / USB
Multimedia	
<ul style="list-style-type: none"> Audio In/Out 	Yes
Video interfaces	
<ul style="list-style-type: none"> Graphics interface 	2x DisplayPort
Industrial Ethernet	
<ul style="list-style-type: none"> Industrial Ethernet interface <ul style="list-style-type: none"> — 100 Mbps — 1000 Mbps 	2x Gigabit Ethernet (RJ45) Yes Yes
Integrated Functions	
Monitoring functions	
<ul style="list-style-type: none"> Temperature monitoring Watchdog Fan 	Yes Yes Yes

• Monitoring function via network	Optional
EMC	
Interference immunity against discharge of static electricity	
• Interference immunity against discharge of static electricity	±6 kV contact; ±8 kV air (to IEC 61000-4-2, ESD)
Interference immunity against high-frequency electromagnetic fields	
• Interference immunity against high frequency radiation	10 V/m for 80 ... 2 700 MHz, 80% AM acc. to IEC 61000-4-3; 3 V/m for 2.7 to 6 GHz, 80% AM acc. to IEC 61000-4-3; 10 V for 10 kHz to 80 MHz, 80% AM acc. to IEC 61000-4-6
Interference immunity to cable-borne interference	
• Interference immunity on supply cables	±2 kV (according to IEC 61000-4-4, burst); ±1 kV (according to IEC 61000-4-5, surge pulse/line to line); ±2 kV (according to IEC 61000-4-5, surge pulse/line to ground)
• Interference immunity on signal cables >30m	burst: ±2 kV (5 kHz / 100 kHz) in accordance with IEC 61000-4-4; length of signal port extension cable ≥ 30 m; surge: ±2 kV line-to-earth in accordance with IEC 61000-4-5; length of signal port extension cable ≥ 10 m
• Interference immunity on signal cables < 30m	burst: ±1 kV (5 kHz / 100 kHz) in accordance with IEC 61000-4-4; length of signal port extension cable < 30 m; surge: ±2 kV line-to-earth in accordance with IEC 61000-4-5; length of signal port extension cable ≥ 10 m
Interference immunity to magnetic fields	
• Interference immunity to magnetic fields at 50 Hz	100 A/m; to IEC 61000-4-8
Emission of conducted and non-conducted interference	
• Interference emission via line/AC current cables	EN 61000-6-3, EN 61000-6-4, CISPR 22 Class B, FCC Class A
Compliance with line harmonic distortion limits	
• Compliance with line harmonic distortion acc. to IEC 61000-3-2, IEC 61000-3-3	Yes; EN 61000-3-2 Class D; EN 61000-3-3
Degree and class of protection	
IP degree of protection	IP20 with fan, IP40 without fan
Standards, approvals, certificates	
CE mark	Yes; also UKCA
cULus	Yes
RCM (formerly C-TICK)	Yes
FCC	Yes
EMC	EMC EN 61000-6-1, EN IEC 61000-6-1, EN 61000-6-2, EN IEC 61000-6-3, EN IEC 61000-6-4
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	55 °C; base module only: 40 °C at fanless and 2.5" non power loss protection SSD configuration; 50 °C at fanless and M.2 SSD configuration; with extension module: 40 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Relative humidity	
• Relative humidity	tested according to IEC 60068-2-78, IEC 60068-2-30: operation: 5 % to 85 % at 30 °C (no condensation) storage: 5 % to 95 % at 25 °C / 55 °C (no condensation)
Vibrations	
• Vibration resistance during operation acc. to IEC 60068-2-6	tested in accordance with IEC 60068-2-6; operation - base module (5 to 8.4 Hz: 3.5 mm; 8.4 to 200 Hz: 9.8 m/s ²); extension module w/o storages (10 to 58 Hz: 0.0375 mm; 58 to 200 Hz: 4.9 m/s ²); extension module with HDD (10 to 58 Hz: 0.015 mm; 58 to 200 Hz: 1.96 m/s ²); extension module with SSD (10 to 58 Hz: 0.0375 mm; 58 to 200 Hz: 4.9 m/s ²); storage / transport - 5 to 8.4 Hz: 3.5 mm; 8.4 to 500 Hz: 9.8 m/s ²
Shock testing	
• Shock load during operation	tested in accordance with IEC 60068-2-27; operation - base module (150 m/s ² , 11 ms); extension module w/o HDD (150 m/s ² , 11 ms); extension module with HDD (10 m/s ² , 20 ms); storage / transport - 250 m/s ² , 6 ms
Operating systems	
pre-installed operating system	Windows 10 Enterprise 2021 LTSC 64-bit, MUI
without operating system	Yes; Optional
pre-installed operating system	
• Windows 10 Enterprise	Yes; Windows 10 Enterprise 2021 LTSC 64-bit, MUI
Dimensions	
Width	79 mm; 85 mm base module with fan module, 137 mm with extension module 2 slots

Height	194 mm
Depth	237 mm; 307 mm base module with fan module and with / without extension module 2 slots

last modified: 10/28/2024 