



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : **1PH8135-1HG22-2BA2-Z**
K24+V90

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	31.0	129.0	61.0	397	78.1	2,300	320	148.0	8,000	170.0	73	0.933	0.850	24.1
	BLM/SLM 400V	29.0	138.0	64.0	348	68.3	2,000	320	148.0	8,000	170.0	73	0.924	0.860	23.9
	ALM/BLM/SLM 480V	32.0	115.0	58.0	448	89.6	2,650	320	148.0	8,000	170.0	73	0.942	0.840	23.0

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	132
Cooling	Water cooling
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP65
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Primer (pale green)
Type of the bearing	Standard with fixed bearing
Shaft end	Feather key with half key balancing
Encoder system	Incremental encoder HTL 1024 S/R, max. encoder speed = 9000 rpm

Cooling water specification

pH value	6 ... 9
Total hardness	1.7 mmol/l
Electrical conductivity	500 μS/cm
Chloride ions	40 mg/l
Sulfate ions	50 mg/l
Nitrate ions	50 mg/l
Dissolved substances	340 mg/l
Maximum particle size	100 μm
Antifreeze/corrosion protection	20 ... 30 %

Special design

K24	Primer
V90	1PH7-compatible shaft end 42 mm x 110 mm

Physical constants

Thermal time constant	12 min
Moment of inertia	940 kgcm ²
Weight (approx.)	141 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	gk843

Cooling data and sound pressure level

Flow rate, min.	12 l/min
Sound pressure level L _{pA} (1m) motor rated load, tolerance + 3dB	68 dB ¹⁾
Pressure drop	0.9 bar
NDE thread connection	0.375 Inches

¹⁾ at a rated frequency of 4 kHz and a speed range of up to 5000 rpm