

SIPLUS ET 200SP IM155-6PN ST -40 ... +70°C with conformal coating based on 6ES7155-6AA01-0BN0 . Bundle PROFINET IM, IM 155-6PN ST, max. 32 Peripheriemodules and 16 ET 200AL Modules, Single Hot SWAP, Bundle contains: Interface-Module (6AG1155-6AU01-7BN0), Server-Module (6AG1193-6PA00-7AA0), Busadapter BA 2xRJ45 (6AG1193-6AR00-7AA0)



Figure similar

General information	
Product type designation	IM 155-6 PN ST
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> <li>Module swapping during operation (hot swapping)</li> </ul>	Yes; I&M0 to I&M3 Yes; Single hot swapping
Engineering with	
<ul style="list-style-type: none"> <li>PROFINET as of GSD version/GSD revision</li> </ul>	V2.3 / -
Configuration control	
via dataset	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Short-circuit protection	Yes
Mains buffering	

- Mains/voltage failure stored energy time 10 ms

### Input current

Current consumption (rated value)	450 mA
Current consumption, max.	550 mA
Inrush current, max.	3.7 A
$I^2t$	0.09 A <sup>2</sup> ·s

### Power

Infeed power to the backplane bus	4.5 W
-----------------------------------	-------

### Power loss

Power loss, typ.	1.9 W
------------------	-------

### Address area

#### Address space per module

- Address space per module, max. 256 byte; per input / output

#### Address space per station

- Address space per station, max. 512 byte; Dependent on configuration

### Hardware configuration

#### Rack

- Modules per rack, max. 32; + 16 ET 200AL modules

#### Submodules

- Number of submodules per station, max. 256

### Interfaces

Number of PROFINET interfaces	1; 2 ports (switch)
-------------------------------	---------------------

### 1. Interface

#### Interface types

- Number of ports 2
- integrated switch Yes
- RJ 45 (Ethernet) Yes; Pre-assembled BusAdapter BA 2x RJ45
- BusAdapter (PROFINET) Yes; Applicable BusAdapter: BA 2x RJ45, BA 2x FC

#### Protocols

- PROFINET IO Device Yes
- Open IE communication Yes
- Media redundancy Yes; PROFINET MRP

### Interface types

#### RJ 45 (Ethernet)

- Transmission procedure PROFINET with 100 Mbit/s full duplex (100BASE-TX)
- 10 Mbps Yes; for Ethernet services
- 100 Mbps Yes; PROFINET with 100 Mbit/s full duplex (100BASE-TX)
- Autonegotiation Yes
- Autocrossing Yes

Protocols	
PROFINET IO Device	
Services	
— Isochronous mode	No
— Open IE communication	Yes
— IRT	Yes; with send cycles of between 250 $\mu$ s and 4 ms in increments of 125 $\mu$ s
— PROFINergy	Yes
— Prioritized startup	Yes
— Shared device	Yes
— Number of IO Controllers with shared device, max.	2
Redundancy mode	
• MRP	Yes
• MRPD	No
• PROFINET system redundancy (S2)	No
Open IE communication	
• TCP/IP	Yes
• SNMP	Yes
• LLDP	Yes
Isochronous mode	
Isochronous operation (application synchronized up to terminal)	No
Interrupts/diagnostics/status information	
Status indicator	Yes
Alarms	Yes
Diagnostics function	Yes
Diagnostics indication LED	
• RUN LED	Yes; green LED
• ERROR LED	Yes; red LED
• MAINT LED	Yes; Yellow LED
• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
• Connection to network LINK (green)	Yes; 2x green link LEDs on BusAdapter
Potential separation	
between backplane bus and electronics	No
between PROFINET and all other circuits	Yes; 1 500 V AC
between supply and all other circuits	No
Permissible potential difference	
between different circuits	Safety extra low voltage SELV
Standards, approvals, certificates	

Network loading class	2
Security level	According to Security Level 1 Test Cases V1.1.1
<b>Ambient conditions</b>	
<b>Ambient temperature during operation</b>	
<ul style="list-style-type: none"> <li>• horizontal installation, min.</li> <li>• horizontal installation, max.</li> <li>• vertical installation, min.</li> <li>• vertical installation, max.</li> </ul>	<p>-40 °C; = Tmin (incl. condensation/frost)</p> <p>70 °C; = Tmax</p> <p>-40 °C; = Tmin</p> <p>50 °C; = Tmax</p>
<b>Altitude during operation relating to sea level</b>	
<ul style="list-style-type: none"> <li>• Installation altitude above sea level, max.</li> <li>• Ambient air temperature-barometric pressure-altitude</li> </ul>	<p>5 000 m</p> <p>Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)</p>
<b>Relative humidity</b>	
<ul style="list-style-type: none"> <li>• With condensation, tested in accordance with IEC 60068-2-38, max.</li> </ul>	100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation
<b>Resistance</b>	
<b>Coolants and lubricants</b>	
— Resistant to commercially available coolants and lubricants	Yes; Incl. diesel and oil droplets in the air
<b>Use in stationary industrial systems</b>	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust; *
<b>Use on ships/at sea</b>	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
<b>Usage in industrial process technology</b>	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
<b>Remark</b>	

— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04

\* The supplied plug covers must remain in place over the unused interfaces during operation!

#### Conformal coating

- Coatings for printed circuit board assemblies acc. to EN 61086
- Protection against fouling acc. to EN 60664-3
- Military testing according to MIL-I-46058C, Amendment 7
- Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A

Yes; Class 2 for high availability

Yes; Type 1 protection

Yes; Discoloration of coating possible during service life

Yes; Conformal coating, Class A

#### Connection method

##### ET-Connection

- via BU/BA Send

Yes; + 16 ET 200AL modules

#### Dimensions

Width	50 mm
Height	117 mm
Depth	74 mm

#### Weights

Weight, approx. 190 g; IM 155-6 PN BA with 2x RJ45 ports and server module

**last modified:**

02/24/2020