

Terminal module for ET 200S RS for reversing starter with supply line connection



Figure similar

General technical data:		
Product designation		Terminal module
Product type designation		TM-RS90-S32
Design of the product		for RS1-x, with energy bus infeed, with caps
Mounting height	mm	264
Installation width	mm	90
Installation depth	mm	100
Protection class IP		IP20
Insulation voltage rated value	V	690
Operating voltage		
• at AC rated value	V	500
Surge voltage resistance rated value	V	6 000
Operating current rated value	A	40
Operating frequency		
• 1 rated value	Hz	50
• 2 rated value	Hz	60
Type of connectable conductor cross-sections		

- solid
- finely stranded with core end processing
- at AWG conductors
  - solid
  - stranded

	1x 10 mm <sup>2</sup> , 2x (1 ... 2.5 mm <sup>2</sup> ), 2x (2.5 ... 6 mm <sup>2</sup> )
	2x (1 ... 2.5 mm <sup>2</sup> ), 2x (2.5 ... 6 mm <sup>2</sup> ), acc. to IEC 60947
	2x (14 ... 10)
	2x (14 ... 10)

**Installation/ mounting/ dimensions:**

<b>Size of the screwdriver tip</b>		Standard screwdriver Size 2
Tightening torque with screw-type terminals	N·m	2 ... 2.5

**Further information**

**Information- and Downloadcenter (Catalogs, Brochures,...)**  
<http://www.siemens.com/industrial-controls/catalogs>

**Industry Mall (Online ordering system)**  
<http://www.siemens.com/industrymall>

**Cax online generator**  
<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK1903-0AC00>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**  
<https://support.industry.siemens.com/cs/ww/en/ps/3RK1903-0AC00>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**  
[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RK1903-0AC00&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK1903-0AC00&lang=en)





last modified:

09/13/2019