

SIMATIC PCS 7-400, UR2-H XTR S7-400 rack central and distributed with 2 x 9 slots, 2 x 2 redundant PS can be plugged in for extended temperature range and with conformal coating

| General information                               |  |
|---|--|
| Product type designation                          | UR2-H XTR  |
| Rack design                                       | With Conformal Coating (ISA-S71.04 severity level G1; G2; G3) and operating temperature to 70 °C |
| Hardware configuration                            |  |
| Rack  |  |
| • Communication bus                               | Yes; Separated   |
| • P bus   | Yes; Separated   |
| Slots   |  |
| • Number of slots                                 | 18; 2 segments with 9 slots each   |
| Standards, approvals, certificates                |  |
| CE mark   | Yes  |
| UL approval                                       | Yes  |
| FM approval                                       | Yes  |
| RCM (formerly C-TICK)                             | Yes  |
| KC approval                                       | Yes  |
| EAC (formerly Gost-R)                             | Yes  |
| Ambient conditions                                |  |
| Ambient temperature during operation              |  |
| • min.  | 0 °C   |
| • max.  | 70 °C  |
| Ambient temperature during storage/transportation |  |
| • min.  | 0 °C   |
| • max.  | 70 °C  |
| Dimensions  |  |
| Width   | 482.5 mm   |
| Height  | 290 mm   |
| Depth   | 27.5 mm  |
| Weights   |  |
| Weight, approx.                                   | 3 000 g  |
| last modified:                                    | 02/07/2020   |