

Data sheet for SIMOTICS S-1FT7



Figure similar

MLFB-Ordering data

1FT7036-5AK71-1CH2-Z
Q13

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data		Mechanical data	
Rated speed	6000 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	6	Design of the motor type	Compact
Rated torque (100 K)	1.7 Nm	Shaft height	36 mm
Rated current	2.4 A	Cooling	Natural cooling
Static torque (60 K)	2.40 Nm	Radial runout tolerance	N
Static torque (100 K)	3.0 Nm	Vibration severity grade	Grade A
Stall current (60 K)	3.1 A	Degree of protection	IP67
Stall current (100 K)	4.0 A	Design acc. to Code I	IM B5 (compatible with 1FT6)
Rotor moment of inertia	0.0001450 kgm ²	Temperature monitoring	Pt1000 temperature sensor
Efficiency	90.0 %	Color of the housing	
Physical constants		Holding brake version	Permanent-magnet brake
Torque constant	0.76 Nm/A	Shaft end type	Plain shaft
Voltage constant at 20° C	48.5 V/1000*min ⁻¹	Sensor design	Encoder AM24DQI: Absolute encoder 24 bit (resolution 16777216, encoder-internal 2048 S/R) + 12 bit Multiturn (traversing range 4096 revolutions) - with signal connection RJ45
Winding resistance at 20° C	1.37 Ω	Electrical connectors	Connector turnable
Rotating field inductance	5.9 mH	Connector size	1
Electrical time constant	4.30 ms		
Mechanical time constant	1.00 ms		
Thermal time constant	30 min		
Shaft torsional stiffness	3150 Nm/rad		
Net weight of the motor	5.4 kg		

Data sheet for SIMOTICS S-1FT7

MLFB-Ordering data 1FT7036-5AK71-1CH2-Z
Q13




Figure similar

Optimum operating point		Recommended Motor Module	
Optimum speed	6000 rpm	Rated inverter current	5 A
Optimum power	1.1 kW	Maximum inverter current	15 A
Limiting data		Maximum torque	10.80 Nm
Max. permissible speed (mech.)	10000 rpm	Special design	
Max. permissible speed (inverter)	10000 rpm	Q13	Customized additional sealing
Maximum torque	12.0 Nm		
Maximum current	17.0 A		