

## Data sheet for SIMOTICS S-1FK7



Figure similar

MLFB-Ordering data

1FK7105-2AC71-1SG2

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

| Engineering data          |                           | Mechanical data             |   |  |  |
|---------------------------|---------------------------|-----------------------------|---|--|--|
| Rated speed (100 K)       | 2000 rpm                  | Motor type                  | Permanent-magnet synchronous motor  |  |  |
| Number of poles           | 8                         | Motor type                  | Compact   |  |  |
| Rated torque (100 K)      | 37.0 Nm                   | Shaft height                | 100   |  |  |
| Rated current             | 16.0 A                    | Cooling                     | Natural cooling   |  |  |
| Static torque (60 K)      | 40.00 Nm                  | Radial runout tolerance     | 0.050 mm  |  |  |
| Static torque (100 K)     | 48.0 Nm                   | Concentricity tolerance     | 0.10 mm   |  |  |
| Stall current (60 K)      | 16.20 A                   | Axial runout tolerance      | 0.10 mm   |  |  |
| Stall current (100 K)     | 20.00 A                   | Vibration severity grade    | Grade A   |  |  |
| Moment of inertia         | 154.000 kgcm <sup>2</sup> | Connector size              | 1.5   |  |  |
| Efficiency                | 93.0 %                    | Degree of protection        | IP65 and DE flange IP67   |  |  |
| <b>Physical constants</b> |                           | Design acc. to Code I       | IM B5 (IM V1, IM V3)  |  |  |
|                           |                           | Temperature monitoring      | KTY84 temperature sensor in the stator winding  |  |  |
|                           |                           | Electrical connectors       | Connectors for signals and power rotatable  |  |  |
|                           |                           | Color of the housing        | Standard (Anthracite RAL 7016)  |  |  |
|                           |                           | Holding brake               | without holding brake   |  |  |
|                           |                           | Shaft extension             | Plain shaft   |  |  |
|                           |                           | Encoder system              | Multi-pole resolver (number of pole pairs corresponds to number of pole pairs of the motor) |  |  |
|                           |                           | Torque constant             | 2.37 Nm/A   |  |  |
|                           |                           | Voltage constant at 20° C   | 157.5 V/1000*min <sup>-1</sup>  |  |  |
|                           |                           | Winding resistance at 20° C | 0.17 Ω  |  |  |
| Rotating field inductance | 4.5 mH                    |                             |   |  |  |
| Electrical time constant  | 25.50 ms                  |                             |   |  |  |
| Mechanical time constant  | 1.40 ms                   |                             |   |  |  |
| Thermal time constant     | 70 min                    |                             |   |  |  |
| Shaft torsional stiffness | 125000 Nm/rad             |                             |   |  |  |
| Net weight of the motor   | 39.0 kg                   |                             |   |  |  |



Figure similar

MLFB-Ordering data

1FK7105-2AC71-1SG2

| Optimum operating point           |          | Recommended Motor Module |           |
|-----------------------------------|----------|--------------------------|-----------|
| Optimum speed                     | 2000 rpm | Rated inverter current   | 30 A      |
| Optimum power                     | 7.7 kW   | Maximum inverter current | 72 A      |
| Limiting data                     |          | Maximum torque           | 150.00 Nm |
| Max. permissible speed (mech.)    | 5000 rpm |                          |           |
| Max. permissible speed (inverter) | 3650 rpm |                          |           |
| Maximum torque                    | 150.0 Nm |                          |           |
| Maximum current                   | 71.0 A   |                          |           |