



Figure similar

## MOTION CONNECT 800PLUS

### MLFB-Ordering data

6FX8002-5CP17-1BF0

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Electrical data

No. of cores x cross-section mm <sup>2</sup>	4x2.5 C
Test voltage, rms Power conductors	4.0 kV
Test voltage, rms Signal conductors	2.0 kV
Type with braking lead	No
Rated voltage V0/V according to EN 50395	600 V/1000 V

### Mechanical data

Type of connection cable engine side	Open end of lead
Connector size	without
Type of bolting	M25
Type of connection cable converter side	Connector for SINAMICS S120 Booksize MoMo, C/D types
Maximum cable outer diameter	11.0 mm
Length	15.0 m
Weight (without connector)	3.00 kg

### Static deployment

Smallest bending radius (fixed installation)	44.0 mm
Tensile stress, max. Fixed installation	50 N/mm <sup>2</sup> (7252 lbf/in <sup>2</sup> )
Torsional stress	Absolute 30°/m

### Dynamic deployment

Smallest bending radius(flexible installation in a cable carriers)	90.0 mm
Acceleration horizontal, max	50 m/s <sup>2</sup>
Maximum traversing velocity	300 m/min
Travel path	50 m
Number of bends, max.	10,000,000
Tensile load for moving cable, max.	20 N/mm <sup>2</sup> (2901 lbf/in <sup>2</sup> )



Figure similar

MLFB-Ordering data

6FX8002-5CP17-1BF0

## Technical data

### Ambient temperature

Operation with permanently installed cable	-50 ... 80 °C
	Module-end power connector 0 ... 55°C, Motor-end power connector -20 ... 80°C
Operation with moving cable	-20 ... 60 °C
	Module-end power connector 0 ... 55°C
Storage	-20 ... 80 °C
	Module-end power connector -20 ... 70°C, Motor-end power connector -20 ... 80°C

Kind of connection cable	Basis cable
Material of the cable sheath	PUR DESINA color orange RAL 2003
Type of insulation	CFC/halogen/silicone-free
Standard for behavior in fire: flame resistance	EN 60332-1-1 to 1-3
Oil resistance	EN 60811-2-1
Verification of suitability as authorisation for USA	UL 758
Verification of suitability as authorisation for Canada	CSA-C22.2-N.210.2-M90