

30mm BlackMax, Epoxy Coated Corrosion Resistant Metal Operator, Round Non-Illuminated Selector Switch, Short Lever Black with White Insert 4 Position, H-CAM Maintained UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards



Figure similar

<b>Design of the product</b>	Actuator round
<b>Enclosure</b>	
<b>Number of command points</b>	1
<b>Delivery state</b>	No
<ul style="list-style-type: none"> <li>as a kit</li> </ul>	
<b>Actuator</b>	
<b>Design of the operating mechanism</b>	selector switch
<b>Material of the actuating element</b>	plastic
<b>Type of unlocking device</b>	rotate-to-unlatch mechanism
<b>Number of switching positions</b>	4
<b>Front ring</b>	
<b>Product component front ring</b>	Yes
<b>Design of the front ring</b>	standard
<b>Material of the front ring</b>	metal
<b>Color of the front ring</b>	black
<b>Holder</b>	

Material of the holder	Metal
------------------------	-------

#### General technical data

Product component	
• Light source	No
Degree of pollution	1
Protection class IP	IP66
Operating frequency maximum	600 1/h

#### Ambient conditions

Ambient temperature	
• during operation	-35 ... +70 °C
• during storage	-40 ... +85 °C

#### Installation/ mounting/ dimensions

Shape of the installation opening	round
-----------------------------------	-------

#### Certificates/ approvals

#### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

[www.siemens.com/sirius/catalogs](http://www.siemens.com/sirius/catalogs)

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SX2HAB>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SX2HAB>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52SX2HAB>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=US2:52SX2HAB&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SX2HAB&lang=en)

last modified:

11/13/2019