



Figure similar

MLFB-Ordering data

1FK7042-3BK71-1EA1

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data		Mechanical data			
Rated speed (100 K)	6000 rpm	Motor type	Permanent-magnet synchronous motor		
Number of poles	8	Motor type	High Inertia		
Rated torque (100 K)	1.5 Nm	Shaft height	48		
Rated current	2.5 A	Cooling	Natural cooling		
Static torque (60 K)	2.50 Nm	Radial runout tolerance	0.040 mm		
Static torque (100 K)	3.0 Nm	Concentricity tolerance	0.08 mm		
Stall current (60 K)	3.55 A	Axial runout tolerance	0.08 mm		
Stall current (100 K)	4.40 A	Vibration severity grade	Grade A		
Moment of inertia	5.100 kgcm <sup>2</sup>	Connector size	1		
Efficiency	89.0 %	Degree of protection	IP65		
<th colspan="2">Physical constants</th> <td>Design acc. to Code I</td> <td>IM B5 (IM V1, IM V3)</td>		Physical constants		Design acc. to Code I	IM B5 (IM V1, IM V3)
		Torque constant	0.68 Nm/A	Temperature monitoring	KTY84 temperature sensor in the stator winding
		Voltage constant at 20° C	44.5 V/1000*min <sup>-1</sup>	Electrical connectors	Connectors for signals and power rotatable
		Winding resistance at 20° C	1.15 Ω	Color of the housing	Standard (Anthracite RAL 7016)
		Rotating field inductance	8.6 mH	Holding brake	without holding brake
		Electrical time constant	7.50 ms	Shaft extension	Feather key
		Mechanical time constant	3.80 ms	Encoder system	Encoder AM2048S/R: absolute encoder 2048 S/R, 4096 revolutions multi-turn, with EnDat interface
		Thermal time constant	30 min		
		Shaft torsional stiffness	14600 Nm/rad		
		Net weight of the motor	5.1 kg		



Figure similar

MLFB-Ordering data

1FK7042-3BK71-1EA1

### Optimum operating point

Optimum speed 5000 rpm

Optimum power 1.0 kW

### Limiting data

Max. permissible speed (mech.) 9000 rpm

Max. permissible speed (inverter) 9000 rpm

Maximum torque 10.5 Nm

Maximum current 15.3 A

### Recommended Motor Module

Rated inverter current 5 A

Maximum inverter current 15 A

Maximum torque 10.30 Nm