

## Data sheet for SIMOTICS S-1FT7



Figure similar

MLFB-Ordering data

1FT7108-5WC71-4CH1-Z  
J25

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data		Mechanical data																					
Rated speed	2000 rpm	Motor type	Permanent-magnet synchronous motor																				
Number of poles	10	Design of the motor type	Compact																				
Rated torque (100 K)	125.0 Nm	Shaft height	100 mm																				
Rated current	47.5 A	Cooling	Water cooling																				
Static torque (60 K)	100.00 Nm	Radial runout tolerance	N																				
Static torque (100 K)	125.0 Nm	Vibration severity grade	Grade A																				
Stall current (60 K)	37.2 A	Connector size	3																				
Stall current (100 K)	45.3 A	Degree of protection	IP65																				
Rotor moment of inertia	0.0313200 kgm <sup>2</sup>	Design acc. to Code I	IM B5 (compatible with 1FT6)																				
<table border="1"> <thead> <tr> <th colspan="2">Physical constants</th> </tr> </thead> <tbody> <tr> <td>Torque constant</td> <td>2.69 Nm/A</td> </tr> <tr> <td>Voltage constant at 20° C</td> <td>170.0 V/1000*min<sup>-1</sup></td> </tr> <tr> <td>Winding resistance at 20° C</td> <td>0.08 Ω</td> </tr> <tr> <td>Rotating field inductance</td> <td>1.9 mH</td> </tr> <tr> <td>Electrical time constant</td> <td>23.00 ms</td> </tr> <tr> <td>Mechanical time constant</td> <td>0.90 ms</td> </tr> <tr> <td>Thermal time constant</td> <td>2 min</td> </tr> <tr> <td>Shaft torsional stiffness</td> <td>96000 Nm/rad</td> </tr> <tr> <td>Net weight of the motor</td> <td>106.9 kg</td> </tr> </tbody> </table>		Physical constants		Torque constant	2.69 Nm/A	Voltage constant at 20° C	170.0 V/1000*min <sup>-1</sup>	Winding resistance at 20° C	0.08 Ω	Rotating field inductance	1.9 mH	Electrical time constant	23.00 ms	Mechanical time constant	0.90 ms	Thermal time constant	2 min	Shaft torsional stiffness	96000 Nm/rad	Net weight of the motor	106.9 kg	Temperature monitoring	Pt1000 temperature sensor
		Physical constants																					
Torque constant	2.69 Nm/A																						
Voltage constant at 20° C	170.0 V/1000*min <sup>-1</sup>																						
Winding resistance at 20° C	0.08 Ω																						
Rotating field inductance	1.9 mH																						
Electrical time constant	23.00 ms																						
Mechanical time constant	0.90 ms																						
Thermal time constant	2 min																						
Shaft torsional stiffness	96000 Nm/rad																						
Net weight of the motor	106.9 kg																						
		Electrical connectors	Axial DE																				
		Color of the housing																					
		Holding brake version	Permanent-magnet brake																				
		Shaft end type	Plain shaft																				
		Sensor design	Encoder AM24DQI: Absolute encoder 24 bit (resolution 16777216, encoder-internal 2048 S/R) + 12 bit Multiturn (traversing range 4096 revolutions) - with signal connection RJ45																				
<table border="1"> <thead> <tr> <th colspan="2">Recommended Motor Module</th> </tr> </thead> <tbody> <tr> <td>Rated inverter current</td> <td>45 A</td> </tr> <tr> <td>Maximum inverter current</td> <td>85 A</td> </tr> <tr> <td>Maximum torque</td> <td>214.00 Nm</td> </tr> </tbody> </table>				Recommended Motor Module		Rated inverter current	45 A	Maximum inverter current	85 A	Maximum torque	214.00 Nm												
Recommended Motor Module																							
Rated inverter current	45 A																						
Maximum inverter current	85 A																						
Maximum torque	214.00 Nm																						



Figure similar

MLFB-Ordering data

1FT7108-5WC71-4CH1-Z  
J25

### Gearbox data

Gearbox type	Planetary gearbox	Moment of inertia of gearbox	0.0022200 kgm <sup>2</sup>
Designation	SP 180S-MF1	Radial output shaft loading, max.	14700 N
Gearbox ratio	7	Axial output shaft load, max.	14150 N
Motor speed S3-60 %	3500 rpm	Efficiency of gearbox	0.97
Motor speed S1	2300 rpm	Torsional backlash	3 '
Output torque S1	750 Nm	Gearbox weight	34.00 kg
Rated output torque at duty type S3-60 %	1100 Nm		

### Limiting data

Max. permissible speed (mech.)	6000 rpm
Max. permissible speed (inverter)	3400 rpm
Maximum torque	330.0 Nm
Maximum current	141.5 A

### Special design

J25 Mounting of SP+ planetary gearbox