



Figure similar

## Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8107-1SF02-3LA1

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

		$P_N$ [kW]	$M_N$ [Nm]	$I_N$ [A]	$U_N$ [V]	$f_N$ [Hz]	$n_N$ [rpm]	$M_{max}$ [Nm]	$I_{max}$ [A]	$n_{max}$ [rpm]	$M_0$ [Nm]	$I_0$ [A]	$\eta$	$\cos \phi$	$I\mu$ [A]
Y	ALM 400V	10.0	55.0	22.0	380	60.4	1,750	135	54.0	12,000	63.0	25	0.878	0.800	10.9
	BLM/SLM 400V	9.0	57.0	23.5	330	52.2	1,500	135	54.0	12,000	63.0	25	0.869	0.810	10.8
	ALM/BLM/SLM 480V	11.0	53.0	21.5	428	68.6	2,000	135	54.0	12,000	63.0	25	0.901	0.790	10.8

### Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	100
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	SPECIAL/B
Shaft and flange accuracy	SPECIAL
Degree of protection	IP55
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Performance
Shaft extension	Smooth hollow shaft
Encoder system	Incremental encoder 19 bit without commutation position (encoder IN19DQ)

### Physical constants

Thermal time constant	20 min
Moment of inertia	289 kgcm <sup>2</sup>
Weight (approx.)	73 kg

### Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	gk813

### Cooling data and sound pressure level

Airflow, min.	0.04 m <sup>3</sup> /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	70 dB <sup>1)</sup>
Air discharge	axial
Pressure drop	110 Pa

<sup>1)</sup> at a rated frequency of 4 kHz and a speed range of up to 5000 rpm