

Data sheet for SIMOTICS S-1FK7

MLFB-Ordering data

1FK7083-5AF71-1UG3-Z
K23

No image
available for this
configuration.

Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data		Mechanical data			
Rated speed (100 K)	3000 rpm	Motor type	Permanent-magnet synchronous motor		
Number of poles	8	Motor type	Compact		
Rated torque (100 K)	10.5 Nm	Shaft height	80		
Rated current	7.4 A	Cooling	Natural cooling		
Static torque (60 K)	13.30 Nm	Radial runout tolerance	0.050 mm		
Static torque (100 K)	16.0 Nm	Concentricity tolerance	0.10 mm		
Stall current (60 K)	8.60 A	Axial runout tolerance	0.10 mm		
Stall current (100 K)	10.40 A	Vibration severity grade	Grade A		
Moment of inertia	27.300 kgcm ²	Connector size	1		
Efficiency	93.0 %	Degree of protection	IP64		
<th colspan="2">Physical constants</th>		Physical constants		Design acc. to Code I	IM B5 (IM V1, IM V3)
		Torque constant	1.52 Nm/A	Temperature monitoring	KTY84 temperature sensor in the stator winding
		Voltage constant at 20° C	97.0 V/1000*min ⁻¹	Electrical connectors	Connectors for signals and power rotatable
		Winding resistance at 20° C	0.40 Ω	Color of the housing	Standard (Anthracite RAL 7016)
		Rotating field inductance	6.0 mH	Holding brake	without holding brake
		Electrical time constant	15.50 ms	Shaft extension	Plain shaft
		Mechanical time constant	1.41 ms	Encoder system	Resolver R15DQ: resolver 15 bits (resolution 32768, internal multi-pole)
		Thermal time constant	50 min		
		Shaft torsional stiffness	105000 Nm/rad		
		Net weight of the motor	14.0 kg		

MLFB-Ordering data

1FK7083-5AF71-1UG3-Z
K23

Figure similar

Optimum operating point

Optimum speed	3000 rpm
Optimum power	3.3 kW

Limiting data

Max. permissible speed (mech.)	6000 rpm
Max. permissible speed (inverter)	5900 rpm
Maximum torque	50.0 Nm
Maximum current	37.0 A

Recommended Motor Module

Rated inverter current	9 A
Maximum inverter current	18 A
Maximum torque	27.80 Nm

Special design

K23 Special painting for climate group Worldwide: Primer and varnish