

Data sheet for SIMOTICS S-1FT7



Figure similar

MLFB-Ordering data

1FT7066-5AH71-1FH0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data		Mechanical data	
Rated speed	4500 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	10	Design of the motor type	Compact
Rated torque (100 K)	5.0 Nm	Shaft height	63 mm
Rated current	6.3 A	Cooling	Natural cooling
Static torque (60 K)	10.00 Nm	Radial runout tolerance	N
Static torque (100 K)	12.0 Nm	Vibration severity grade	Grade A
Stall current (60 K)	11.3 A	Degree of protection	IP64
Stall current (100 K)	13.6 A	Design acc. to Code I	IM B5 (compatible with 1FT6)
Rotor moment of inertia	0.0019300 kgm ²	Temperature monitoring	Pt1000 temperature sensor
Efficiency	90.0 %	Color of the housing	
Physical constants		Holding brake version	Permanent-magnet brake
Torque constant	0.88 Nm/A	Shaft end type	Plain shaft
Voltage constant at 20° C	56.0 V/1000*min ⁻¹	Sensor design	Encoder AM22DQ: absolute encoder 22 bits (resolution 4194304, encoder-internal 2048 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)
Winding resistance at 20° C	0.20 Ω	Electrical connectors	Connector turnable
Rotating field inductance	2.3 mH	Connector size	1
Electrical time constant	12.00 ms		
Mechanical time constant	1.20 ms		
Thermal time constant	40 min		
Shaft torsional stiffness	24000 Nm/rad		
Net weight of the motor	14.1 kg		

Data sheet for SIMOTICS S-1FT7

MLFB-Ordering data

1FT7066-5AH71-1FH0



Figure similar

Optimum operating point		Recommended Motor Module	
Optimum speed	4000 rpm	Rated inverter current	18 A
Optimum power	2.5 kW	Maximum inverter current	54 A
Limiting data		Maximum torque	42.80 Nm
Max. permissible speed (mech.)	9000 rpm		
Max. permissible speed (inverter)	8000 rpm		
Maximum torque	49.0 Nm		
Maximum current	70.0 A		