

Data sheet for SIMOTICS S-1FK7

MLFB-Ordering data

1FK7060-5AH71-1KB0

No image available for this configuration.

Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

| Engineering data | | Mechanical data | | | |
|---------------------------|--------------------------|-----------------------------|------------------------------------|------------------------|---|
| Rated speed (100 K) | 4500 rpm | Motor type | Permanent-magnet synchronous motor | | |
| Number of poles | 8 | Motor type | Compact | | |
| Rated torque (100 K) | 3.7 Nm | Shaft height | 63 | | |
| Rated current | 4.1 A | Cooling | Natural cooling | | |
| Static torque (60 K) | 5.00 Nm | Radial runout tolerance | 0.040 mm | | |
| Static torque (100 K) | 6.0 Nm | Concentricity tolerance | 0.10 mm | | |
| Stall current (60 K) | 5.10 A | Axial runout tolerance | 0.10 mm | | |
| Stall current (100 K) | 6.20 A | Vibration severity grade | Grade A | | |
| Moment of inertia | 10.200 kgcm ² | Connector size | 1 | | |
| Efficiency | 90.0 % | Degree of protection | IP64 | | |
| Physical constants | | Design acc. to Code I | IM B5 (IM V1, IM V3) | | |
| | | Torque constant | 0.95 Nm/A | Temperature monitoring | KTY84 temperature sensor in the stator winding |
| | | Voltage constant at 20° C | 60.5 V/1000*min ⁻¹ | Electrical connectors | Connectors for signals and power rotatable |
| | | Winding resistance at 20° C | 0.73 Ω | Color of the housing | without |
| | | Rotating field inductance | 7.0 mH | Holding brake | with holding brake |
| | | Electrical time constant | 9.60 ms | Shaft extension | Feather key |
| | | Mechanical time constant | 1.93 ms | Encoder system | Encoder AM16DQ: absolute encoder 16 bits (resolution 65536, encoder-internal 32 S/R) + 12 bits multi-turn (traversing range 4096 revolutions) |
| | | Thermal time constant | 30 min | | |
| | | Shaft torsional stiffness | 42000 Nm/rad | | |
| | | Net weight of the motor | 8.0 kg | | |

MLFB-Ordering data

1FK7060-5AH71-1KB0

Figure similar

Optimum operating point

| | |
|---------------|----------|
| Optimum speed | 4500 rpm |
| Optimum power | 1.7 kW |

Limiting data

| | |
|-----------------------------------|----------|
| Max. permissible speed (mech.) | 7200 rpm |
| Max. permissible speed (inverter) | 9500 rpm |
| Maximum torque | 18.0 Nm |
| Maximum current | 19.5 A |

Holding brake

| | |
|-----------------------|------------------------|
| Holding brake version | Permanent-magnet brake |
| Holding torque | 13.0 Nm |
| Power supply voltage | DC 24 V \pm 10 % |
| Coil current | 0.8 A |
| Opening time | 100 ms |
| Closing time | 50 ms |
| Highest braking work | 380 J |

Recommended Motor Module

| | |
|--------------------------|----------|
| Rated inverter current | 9 A |
| Maximum inverter current | 18 A |
| Maximum torque | 16.80 Nm |