

Article No. : **1FG1601-1RC26-2AU1-Z**  
D14+G23+K08



Figure similar

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Gearbox data


Gear box type	C29
Gearbox basic type	Helical worm geared C
Gearbox size	29
Transmission (ratio)	49.87
Gear number relation	748/15
Output moment maximum (short-time)	126 Nm
max. input speed (briefly)	4,500 rpm
Output speed short-time	90 rpm
Emergency off output moment (1000 cycles)	129 Nm
Radial force maximum	4,170 N
Max. permissible radial force with Mmax	4,050 N
Moment of inertia	0.05 kgcm <sup>2</sup>
Torsional stiffness	-/-
Efficiency	0.88
Mounting position	M4-A
Mounting type	Foot-mounted
Output shaft version	Solid shaft standard
Output shaft dimension	V20 x 40 mm
Gearbox flange diameter	-/-
Output shaft bearing	No
Figure 2 torque support	-

### General tech. specifications

Color of the housing	Standard painting (Anthracite RAL 7016)
Specification	CE / UL / CSA / EAC / cRUus
Net weight	7.86 kg
1m-sound pressure level L <sub>pA</sub> (Tol.+3dB(A))	65
Plug position	top (default) (2)
Adapter flange position	top (default) (2)

### Lubrication and sealing

Gear oil	Polyglycol oil CLP ISO PG VG460
Output shaft sealing	Seal longer service life
Oil charge	0.55 l



### Motor data

Motor type	Permanent-magnet synchronous motor
Motor type	Compact
DC-link voltage, max.	510...720V
Shaft height	36 mm
Cooling	Natural cooling
Rated speed	6,000 rpm
Rated torque (100K)	0.65 Nm
Rated power	0.41 kW
Rated current (100K)	1.09 A
Static torque	1.01 Nm
Static current	1.50 A
Moment of inertia	0.65 kgcm <sup>2</sup>
Efficiency η	87 %
Temperature monitoring	Pt1000 temperature sensor
Connector size	1
Degree of protection	IP65
Encoder system	Encoder AM20DQI: absolute encoder 20 bits (resolution 1048576, encoder-internal 512 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)

### Limiting data

Maximum speed (short-time)	10,000 rpm
Maximum torque	4.50 Nm
Motor current short term	7.0 A

### Optimum operating point

Optimum speed	6,000 rpm
Optimum power	0.41 kW

## Data sheet for SIMOTICS S-1FG1

Article No. : **1FG1601-1RC26-2AU1-Z**  
D14+G23+K08

### Recommended Motor Module

Rated inverter current	3.0 A
Maximum inverter current	9.0 A
Maximum torque	4.5 Nm

### Standards

Compliance with standards	CE / UL / CSA / EAC / cRUus
CE marking	EN 60034

### Options

D14	M4-A for bevel and worm gearboxes
G23	Seal longer service life
K08	Polyglycol oil CLP ISO PG VG460

### Info servo geared motor

Outside the standard temperature range of -10 to +40 °C, further selectable options must be observed, in addition to the lubricant selection.

Further, you have to check the suitability of the components and options used for the requested temperature range.