

Data sheet for SIMOTICS S-1FT7

MLFB-Ordering data

1FT7036-5AK71-1CG2



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data		Mechanical data	
Rated speed	6000 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	6	Design of the motor type	Compact
Rated torque (100 K)	1.7 Nm	Shaft height	36 mm
Rated current	2.4 A	Cooling	Natural cooling
Static torque (60 K)	2.40 Nm	Radial runout tolerance	N
Static torque (100 K)	3.0 Nm	Vibration severity grade	Grade A
Stall current (60 K)	3.1 A	Degree of protection	IP67
Stall current (100 K)	4.0 A	Design acc. to Code I	IM B5 (compatible with 1FT6)
Rotor moment of inertia	0.0001330 kgm ²	Temperature monitoring	Pt1000 temperature sensor
Efficiency	90.0 %	Color of the housing	Standard (pearl dark gray similar to RAL 9023)
Physical constants		Holding brake version	no value
Torque constant	0.76 Nm/A	Shaft end type	Plain shaft
Voltage constant at 20° C	48.5 V/1000*min ⁻¹	Sensor design	Encoder AM24DQI: Absolute encoder 24 bit (resolution 16777216, encoder-internal 2048 S/R) + 12 bit Multiturn (traversing range 4096 revolutions) - with signal connection RJ45
Winding resistance at 20° C	1.37 Ω	Electrical connectors	Connector turnable
Rotating field inductance	5.9 mH	Connector size	1
Electrical time constant	4.30 ms		
Mechanical time constant	1.00 ms		
Thermal time constant	30 min		
Shaft torsional stiffness	3150 Nm/rad		
Net weight of the motor	5.0 kg		

Data sheet for SIMOTICS S-1FT7

MLFB-Ordering data

1FT7036-5AK71-1CG2



Figure similar

Optimum operating point		Recommended Motor Module	
Optimum speed	6000 rpm	Rated inverter current	5 A
Optimum power	1.1 kW	Maximum inverter current	15 A
Limiting data		Maximum torque	10.80 Nm
Max. permissible speed (mech.)	10000 rpm		
Max. permissible speed (inverter)	10000 rpm		
Maximum torque	12.0 Nm		
Maximum current	17.0 A		