

Data sheet for SIMOTICS S-1FT7

MLFB-Ordering data

1FT7034-5AK71-1BG2



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

| Engineering data | | Mechanical data | |
|-----------------------------|-------------------------------|--------------------------|--|
| Rated speed | 6000 rpm | Motor type | Permanent-magnet synchronous motor |
| Number of poles | 6 | Design of the motor type | Compact |
| Rated torque (100 K) | 1.4 Nm | Shaft height | 36 mm |
| Rated current | 2.1 A | Cooling | Natural cooling |
| Static torque (60 K) | 1.60 Nm | Radial runout tolerance | N |
| Static torque (100 K) | 2.0 Nm | Vibration severity grade | Grade A |
| Stall current (60 K) | 2.1 A | Degree of protection | IP67 |
| Stall current (100 K) | 2.7 A | Design acc. to Code I | IM B5 (compatible with 1FT6) |
| Rotor moment of inertia | 0.0000850 kgm ² | Temperature monitoring | Pt1000 temperature sensor |
| Efficiency | 90.0 % | Color of the housing | |
| Physical constants | | Holding brake version | no value |
| Torque constant | 0.76 Nm/A | Shaft end type | Plain shaft |
| Voltage constant at 20° C | 48.5 V/1000*min ⁻¹ | Sensor design | Encoder AS24DQI: Absolut encoder Singleturn 24 bit - with signal connection RJ45 |
| Winding resistance at 20° C | 2.40 Ω | Electrical connectors | Connector turnable |
| Rotating field inductance | 9.7 mH | Connector size | 1 |
| Electrical time constant | 4.00 ms | | |
| Mechanical time constant | 1.10 ms | | |
| Thermal time constant | 25 min | | |
| Shaft torsional stiffness | 3650 Nm/rad | | |
| Net weight of the motor | 3.8 kg | | |

Data sheet for SIMOTICS S-1FT7

MLFB-Ordering data

1FT7034-5AK71-1BG2



Figure similar

| Optimum operating point | | Recommended Motor Module | |
|-----------------------------------|-----------|--------------------------|---------|
| Optimum speed | 6000 rpm | Rated inverter current | 3 A |
| Optimum power | 0.9 kW | Maximum inverter current | 9 A |
| Limiting data | | Maximum torque | 6.30 Nm |
| Max. permissible speed (mech.) | 10000 rpm | | |
| Max. permissible speed (inverter) | 10000 rpm | | |
| Maximum torque | 8.0 Nm | | |
| Maximum current | 12.0 A | | |