

Product type designation

PROFIBUS bus terminal 12M

Bus terminal 12M for PROFIBUS, Transmission rates 9.6 Kbit/s to 12 Mbit/s, Plug-in cable 1.5 m



Transfer rate

Transfer rate

- with PROFIBUS

9.6 kbit/s ... 12 Mbit/s

Interfaces

Number of electrical connections

- for PROFIBUS cables

2

Type of electrical connection

- for PROFIBUS cables

Screw terminals

Mechanical data

Material / of the enclosure

plastic

Design, dimensions and weight

Width

50 mm

Height

138 mm

Depth

53 mm

Net weight

360 g

Mounting type

- 35 mm DIN rail mounting

Yes

Product properties, functions, components / general

Product feature

- silicon-free

Yes

Standards, specifications, approvals

Certificate of suitability

- UL approval

Yes

Further Information / Internet Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/snst>

<http://www.siemens.com/simatic-net>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

last modified:

08/12/2019