

Solid-state contactor 3-phase 3RF3 AC 53 / 5.2 A / 40 °C 48-480 V / 110-230 V AC 2-phase controlled Instantaneous switching Spring-type terminal



Product brand name	SIRIUS
Product designation	solid-state contactor
Product type designation	3RF34

General technical data

Product function	instantaneous switching
Power loss [W] / for rated value of the current / at AC / in hot operating state	10 W
Insulation voltage	600 V
• rated value	
Protection class IP	IP20
Shock resistance / acc. to IEC 60068-2-27	15g / 11 ms
Vibration resistance / acc. to IEC 60068-2-6	2g
Reference code / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750	K
Reference code / acc. to DIN EN 81346-2	Q
Reference code / acc. to DIN EN 61346-2	Q

Main circuit

Number of poles / for main current circuit	3
Number of NO contacts / for main contacts	2

Number of NC contacts / for main contacts	0
Operating voltage / at AC	
• at 50 Hz / rated value	48 ... 480 V
• at 60 Hz / rated value	48 ... 480 V
Operating frequency / rated value	50 ... 60 Hz
Relative symmetrical tolerance / of the operating frequency	10 %
Operating range relative to the operating voltage / at AC	
• at 50 Hz	40 ... 506 V
• at 60 Hz	40 ... 506 V
Operating current / minimum	100 mA
Operating current	
• at AC-3 / at 400 V / rated value	5.2 A
• at AC-53a / at 400 V / at ambient temperature 40 °C / rated value	5.2 A
Operating power	
• at AC-3 / at 400 V / rated value	2.2 kW
Rate of voltage rise / at the thyristor / for main contacts / maximum permissible	1 000 V/ μ s
Blocking voltage / at the thyristor / for main contacts / maximum permissible	1 200 V
Reverse current / of the thyristor	10 mA
Derating temperature	40 °C
Surge current resistance / rated value	200 A
I²t value / maximum	200 A ² ·s
Control circuit/ Control	
Type of voltage / of the control supply voltage	AC
Control supply voltage / 1 / at AC	
• at 50 Hz	110 ... 230 V
• at 60 Hz	110 ... 230 V
Control supply voltage frequency	
• 1 / rated value	50 Hz
• 2 / rated value	60 Hz
Control supply voltage / at AC	
• at 50 Hz / Full-scale value for signal<0> recognition	40 V
• at 60 Hz / Full-scale value for signal<0> recognition	40 V
Control supply voltage	
• at AC / initial value for signal <1> detection	90 V
Symmetrical line frequency tolerance	5 Hz

Operating range factor control supply voltage rated value / at AC / at 50 Hz	
• initial value	0.82
• Full-scale value	1.1
Operating range factor control supply voltage rated value / at AC / at 60 Hz	
• initial value	0.82
• Full-scale value	1.1
Control current / at minimum control supply voltage	
• at AC	2 mA
Control current / at AC / rated value	15 mA
Number of NC contacts / for auxiliary contacts	0
Number of NO contacts / for auxiliary contacts	0
Number of CO contacts / for auxiliary contacts	0

Installation/ mounting/ dimensions	
Mounting position	vertical
Mounting type	screw and snap-on mounting onto 35 mm standard mounting rail
• Side-by-side mounting	Yes
Height	95 mm
Width	45 mm
Depth	100.8 mm
Required spacing / with side-by-side mounting	
• upwards	70 mm
• downwards	50 mm
Installation altitude / at height above sea level / maximum	1 000 m

Connections/ Terminals	
Product function / removable terminal for auxiliary and control circuit	Yes
Type of connectable conductor cross-sections	
• for main contacts	
— solid	2x (0.5 ... 2.5 mm ²)
— finely stranded / with core end processing	2x (0.5 ... 1.5 mm ²)
— finely stranded / without core end processing	2x (0.5 ... 2.5 mm ²)
• at AWG conductors / for main contacts	2x (18 ... 14)
Type of connectable conductor cross-sections	
• for auxiliary and control contacts	
— solid	0.5 ... 1.5 mm ²
— finely stranded / with core end processing	0.5 ... 2.5 mm ²
— finely stranded / without core end processing	0.5 ... 2.5 mm ²

<ul style="list-style-type: none"> • at AWG conductors / for auxiliary and control contacts 	1x (AWG 20 ... 12)
Wire stripping length / of the cable	
<ul style="list-style-type: none"> • for main contacts 	10 mm
<ul style="list-style-type: none"> • for auxiliary and control contacts 	10 mm

UL/CSA ratings

Full-load current (FLA) / for three-phase AC motor	
<ul style="list-style-type: none"> • at 480 V / rated value 	3.4 A
Yielded mechanical performance [hp] / for three-phase AC motor	
<ul style="list-style-type: none"> • at 200/208 V / rated value 	0.5 hp
<ul style="list-style-type: none"> • at 220/230 V / rated value 	0.75 hp
<ul style="list-style-type: none"> • at 460/480 V / rated value 	2 hp

Safety related data

Proportion of dangerous failures / with high demand rate / acc. to SN 31920	50 %
MTTF / with high demand rate	76 y
T1 value / for proof test interval or service life / acc. to IEC 61508	20 y

Ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> • during operation 	-25 ... +60 °C
<ul style="list-style-type: none"> • during storage 	-55 ... +80 °C

Electromagnetic compatibility

Conducted interference	
<ul style="list-style-type: none"> • due to burst / acc. to IEC 61000-4-4 	2 kV / 5 kHz behavior criterion 2
<ul style="list-style-type: none"> • due to conductor-earth surge / acc. to IEC 61000-4-5 	2 kV behavior criterion 2
<ul style="list-style-type: none"> • due to conductor-conductor surge / acc. to IEC 61000-4-5 	1 kV behavior criterion 2
<ul style="list-style-type: none"> • due to high-frequency radiation / acc. to IEC 61000-4-6 	140 dBuV in the frequency range 0.15 ... 80 MHz, behavior criterion 1
Electrostatic discharge / acc. to IEC 61000-4-2	4 kV contact discharging / 8 kV air discharging, behavior criterion 2
Conducted HF-interference emissions / acc. to CISPR11	Class A for industrial environment
Field-bound HF-interference emission / acc. to CISPR11	Class A for industrial environment

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)
www.siemens.com/sirius/catalogs

Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RF3405-2BB24>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RF3405-2BB24>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RF3405-2BB24>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RF3405-2BB24&lang=en

Short-circuit protection, design of the fuse link

https://www.automation.siemens.com/cd-static/material/info/3RF20_eng.pdf

Short-circuit protection, design of the fuse link

https://www.automation.siemens.com/cd-static/material/info/3RF21_eng.pdf

Short-circuit protection, design of the fuse link

https://www.automation.siemens.com/cd-static/material/info/3RF22_eng.pdf

Short-circuit protection, design of the fuse link

https://www.automation.siemens.com/cd-static/material/info/3RF23_eng.pdf

Short-circuit protection, design of the fuse link

https://www.automation.siemens.com/cd-static/material/info/3RF24_eng.pdf





