

Selector swich, metal Spring return left & right Short lever Position, E
Cam 3 position Operator only white insert Non-Illuminated UL file
E22655 in Vol. 6 (7) Sec. 13 (2)

Design of the product	Actuator round
------------------------------	----------------

Enclosure

Number of command points	1
Delivery state	No
<ul style="list-style-type: none"> • as a kit 	

Actuator

Design of the operating mechanism	selector switch
Material of the actuating element	plastic
Type of unlocking device	without
Number of switching positions	3

Front ring

Product component front ring	Yes
Design of the front ring	standard
Material of the front ring	metal
Color of the front ring	chrome

Holder

Material of the holder	Metal
-------------------------------	-------

General technical data

Product component	
<ul style="list-style-type: none"> • Light source 	No
Degree of pollution	1
Protection class IP	IP66
Operating frequency maximum	600 1/h

Ambient conditions

Ambient temperature	
<ul style="list-style-type: none"> • during operation 	-35 ... +70 °C
<ul style="list-style-type: none"> • during storage 	-40 ... +85 °C

Installation/ mounting/ dimensions

Shape of the installation opening	round
--	-------

Certificates/ approvals

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

www.siemens.com/sirius/catalogs

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SA2EDB>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SA2EDB>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52SA2EDB>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SA2EDB&lang=en

last modified:

11/15/2019