

## Data sheet for SIMOTICS S-1FK7

MLFB-Ordering data

1FK7043-7AK71-1KB5

No image available for this configuration.

Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data		Mechanical data			
Rated speed (100 K)	6000 rpm	Motor type	Permanent-magnet synchronous motor		
Number of poles	6	Motor type	High Dynamic		
Rated torque (100 K)	2.0 Nm	Shaft height	48		
Rated current	4.4 A	Cooling	Natural cooling		
Static torque (60 K)	2.50 Nm	Radial runout tolerance	0.040 mm		
Static torque (100 K)	3.1 Nm	Concentricity tolerance	0.08 mm		
Stall current (60 K)	4.80 A	Axial runout tolerance	0.08 mm		
Stall current (100 K)	6.40 A	Vibration severity grade	Grade A		
Moment of inertia	1.140 kgcm <sup>2</sup>	Connector size	1		
Efficiency	90.0 %	Degree of protection	IP65 and DE flange IP67		
<b>Physical constants</b>		Design acc. to Code I	IM B5 (IM V1, IM V3)		
		Torque constant	0.48 Nm/A	Temperature monitoring	KTY84 temperature sensor in the stator winding
		Voltage constant at 20° C	32.0 V/1000*min <sup>-1</sup>	Electrical connectors	Connectors for signals and power rotatable
		Winding resistance at 20° C	0.65 Ω	Color of the housing	Standard (Anthracite RAL 7016)
		Rotating field inductance	9.0 mH	Holding brake	with holding brake
		Electrical time constant	13.80 ms	Shaft extension	Feather key
		Mechanical time constant	0.85 ms	Encoder system	Encoder AM16DQ: absolute encoder 16 bits (resolution 65536, encoder-internal 32 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)
		Thermal time constant	40 min		
		Shaft torsional stiffness	11000 Nm/rad		
		Net weight of the motor	7.0 kg		

MLFB-Ordering data

1FK7043-7AK71-1KB5

Figure similar

### Optimum operating point

Optimum speed	6000 rpm
Optimum power	1.3 kW

### Limiting data

Max. permissible speed (mech.)	8000 rpm
Max. permissible speed (inverter)	13300 rpm
Maximum torque	9.4 Nm
Maximum current	20.0 A

### Holding brake

Holding brake version	Permanent-magnet brake
Holding torque	4.0 Nm
Power supply voltage	DC 24 V $\pm$ 10 %
Coil current	0.5 A
Opening time	70 ms
Closing time	30 ms
Highest braking work	150 J

### Recommended Motor Module

Rated inverter current	9 A
Maximum inverter current	18 A
Maximum torque	8.50 Nm