



Figure similar

SIMATIC ET 200SP HA, Carrier module in single carrier for holding one interface module of the ET 200SP HA incl. server module

General information	
Product type designation	IM carrier module, single
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; Asset data
Supply voltage	
Rated value (DC)	24 V
Hardware configuration	
Slots	
<ul style="list-style-type: none"> <li>Number of slots</li> </ul>	1
Potential separation	
between backplane bus and supply voltage	Yes
Isolation	
Isolation tested with	1 500 V DC/1 min, type test
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> <li>horizontal installation, min.</li> <li>horizontal installation, max.</li> <li>vertical installation, min.</li> <li>vertical installation, max.</li> </ul>	-40 °C 70 °C -40 °C 60 °C
Dimensions	
Width	100 mm
Height	204 mm
Depth	35 mm
Weights	
Weight, approx.	250 g
Classifications	

	Version	Classification
eClass	14	27-24-26-07
eClass	12	27-24-26-07
eClass	9.1	27-24-26-07
eClass	9	27-24-26-07
eClass	8	27-24-26-07
eClass	7.1	27-24-26-07
eClass	6	27-24-26-07
ETIM	9	EC001603
ETIM	8	EC001603

## Approvals / Certificates

## General Product Approval


[Miscellaneous](#)

[KC](#)


## General Product Approval

## For use in hazardous locations


[Declaration of Conformity](#)


## For use in hazardous locations

## Maritime application


[Miscellaneous](#)


## Maritime application

## Environment

[NK / Nippon Kaiji Kyokai](#)

[CCS \(China Classification Society\)](#)

Siemens  
EcoTech



last modified:

7/3/2025