



Pilot light
LED lamp
Red lenses
FOR, REV, LOW, HIGH legends
For use with enclosures with lift-off covers



Image is representative and may not depict the actual product.

| General technical data: | |
|--|--|
| Weight | 0.30 lb. |
| Height x Width x Depth | 96 x 54 x 39 mm |
| Finger-safe | Yes |
| Environmental ratings | NEMA 1 |
| Maximum altitude | (no data) |
| Ambient storage temperature | (-25 to 80)°C / (-13 to 176)°F |
| Ambient operating temperature | (-20 to 60)°C / (-4 to 140)°F |
| Humidity (% non-condensing) | (no data) |
| Country of origin | Mexico |
| Typical operating period | 100,000 h |
| Operating voltage: | |
| 49SDLB7RU | 24 - 240 V AC/DC |
| 49SDLB7RL | 277 V AC 50/60 Hz (with included series resistor) |
| Normal operating limits (% of rated voltage) | 80 - 120 % |
| Lamps: | |
| Number of lamps | 2 |
| Number of lamp holders | 2 |
| Type | Colored LED, w/o transformer |
| Color | Red |
| Maximum consumed current per lamp | 20 mA |
| Maximum inrush current | 3 A |
| Lens: | |
| Number of lenses | 2 |
| Material | Plastic |
| Color | Red |
| Legend: | |
| Material | Synthetic paper label with adhesive back |
| Inscription | FOR, REV, LOW, HIGH |
| Background color / foreground color | Black / white |
| Dimensions | 17 mm wide x 12 mm high |
| Mounting/wiring: | |
| Mounting type | Bracket for use with enclosures with lift-off covers |
| Mounting torque | 25 - 30 lb. in. |
| Wire connection type / torque | Screw-type terminals / 7 lb. in. - 8 lb. in. |
| Solid & stranded conductors | 2 x (18 - 14 AWG) 75°C CU |
| Included | Wires and mounting screws |

Note: The addition of auxiliary contacts, not included, may be required to complete the control circuit.

