

SIMATIC DP, 5 electronic modules for ET 200S, 2 DO Standard 24 V DC/0.5 A, 15 mm width, 5 units per packing unit



Supply voltage

Reverse voltage protection	Yes; when using the same load voltage as on the power module
Load voltage L+	
<ul style="list-style-type: none"> Rated value (DC) 	24 V; From power module
<ul style="list-style-type: none"> Reverse polarity protection 	Yes; polarity reversal can lead to the digital outputs being connected through

Input current

from load voltage L+ (without load), max.	5 mA; Per channel
from backplane bus 3.3 V DC, max.	10 mA

Power loss

Power loss, typ.	0.4 W
------------------	-------

Address area

Address space per module	
<ul style="list-style-type: none"> Address space per module, max. 	1 byte
<ul style="list-style-type: none"> with packing 	2 bit

Digital outputs

Type of digital output	Source output (PNP, current-sourcing)
------------------------	---------------------------------------

Number of digital outputs	2
Short-circuit protection	Yes
• Response threshold, typ.	0.7 to 1.8 A
Limitation of inductive shutdown voltage to	-55 to -60 V, typ. L+()
Controlling a digital input	Yes
Switching capacity of the outputs	
• on lamp load, max.	5 W
Load resistance range	
• lower limit	48 Ω
• upper limit	3 400 Ω
Output voltage	
• for signal "1", min.	L+ (-1 V)
Output current	
• for signal "1" rated value	0.5 A
• for signal "1" permissible range, min.	7 mA
• for signal "1" permissible range, max.	600 mA
• for signal "0" residual current, max.	0.3 mA
Output delay with resistive load	
• "0" to "1", max.	200 μs
• "1" to "0", max.	1.3 ms
Parallel switching of two outputs	
• for uprating	No
• for redundant control of a load	Yes; per module
Switching frequency	
• with resistive load, max.	100 Hz
• with inductive load, max.	2 Hz
• on lamp load, max.	10 Hz
Total current of the outputs	
• Current per module, max.	1 A
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Interrupts/diagnostics/status information	
Diagnostics function	No
Diagnostics indication LED	
• Status indicator digital output (green)	Yes
Parameter	
Remark	1 byte
Potential separation	
Potential separation digital outputs	
• between the channels	No

- between the channels and backplane bus

Yes

Isolation

Isolation tested with

500 V DC

Dimensions

Width

15 mm

Height

81 mm

Depth

52 mm

Weights

Weight, approx.

40 g

last modified:

11/16/2019