

MLFB-Ordering data

1FK7105-5AC71-1KB0

Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data		Mechanical data			
Rated speed (100 K)	2000 rpm	Motor type	Permanent-magnet synchronous motor		
Number of poles	8	Motor type	Compact		
Rated torque (100 K)	37.0 Nm	Shaft height	100		
Rated current	16.0 A	Cooling	Natural cooling		
Static torque (60 K)	40.00 Nm	Radial runout tolerance	0.050 mm		
Static torque (100 K)	48.0 Nm	Concentricity tolerance	0.10 mm		
Stall current (60 K)	17.00 A	Axial runout tolerance	0.10 mm		
Stall current (100 K)	20.00 A	Vibration severity grade	Grade A		
Moment of inertia	169.000 kgcm ²	Connector size	1.5		
Efficiency	93.0 %	Degree of protection	IP64		
<th colspan="2">Physical constants</th>		Physical constants		Design acc. to Code I	IM B5 (IM V1, IM V3)
		Torque constant	2.37 Nm/A	Temperature monitoring	KTY84 temperature sensor in the stator winding
		Voltage constant at 20° C	151.0 V/1000*min ⁻¹	Electrical connectors	Connectors for signals and power rotatable
		Winding resistance at 20° C	0.17 Ω	Color of the housing	without
		Rotating field inductance	4.4 mH	Holding brake	with holding brake
		Electrical time constant	26.00 ms	Shaft extension	Feather key
		Mechanical time constant	1.40 ms	Encoder system	Encoder AM16DQ: absolute encoder 16 bits (resolution 65536, encoder-internal 32 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)
		Thermal time constant	70 min		
		Shaft torsional stiffness	125000 Nm/rad		
		Net weight of the motor	41.5 kg		

MLFB-Ordering data

1FK7105-5AC71-1KB0

Figure similar

Optimum operating point

Optimum speed 2000 rpm

Optimum power 7.8 kW

Limiting data

Max. permissible speed (mech.) 5000 rpm

Max. permissible speed (inverter) 3800 rpm

Maximum torque 150.0 Nm

Maximum current 72.0 A

Holding brake

Holding brake version Permanent-magnet brake

Holding torque 43.0 Nm

Power supply voltage DC 24 V \pm 10 %

Coil current 1.0 A

Opening time 300 ms

Closing time 70 ms

Highest braking work 3380 J

Recommended Motor Module

Rated inverter current 30 A

Maximum inverter current 56 A

Maximum torque 127.00 Nm