

\*\*\* Spare part \*\*\* LOGO! 12/24RCO, logic module PS/I/O: 12/24 V DC/relay, 8 DI (4 AI)/4 DO, without display, memory 200 blocks, modular expandable



### Installation type/mounting

Mounting on 35 mm DIN rail, 4 spacing units wide

### Supply voltage

Rated value (DC)

- 12 V DC Yes
- 24 V DC Yes

permissible range, lower limit (DC) 10.8 V

permissible range, upper limit (DC) 28.8 V

### Time of day

Time switching clocks

- Number 8
- Power reserve 80 h

### Digital inputs

Number of digital inputs 8; Of which 4 can be used in analog mode (0 to 10 V)

### Digital outputs

Number of digital outputs 4; Relays

Short-circuit protection No; external fusing necessary

Relay outputs	
Switching capacity of contacts	
— with inductive load, max.	3 A
— with resistive load, max.	10 A

EMC	
Emission of radio interference acc. to EN 55 011	
• Limit class B, for use in residential areas	Yes

Degree and class of protection	
Degree of protection acc. to EN 60529	
• IP20	Yes

Standards, approvals, certificates	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
FM approval	Yes
developed in accordance with IEC 61131	Yes
according to VDE 0631	Yes
Marine approval	Yes

Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	55 °C

Dimensions	
Width	72 mm
Height	90 mm
Depth	55 mm
<b>last modified:</b>	08/16/2019