

Data sheet for SIMOTICS S-1FT7



Figure similar

MLFB-Ordering data

1FT7084-1AH71-1BG1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data		Mechanical data	
Rated speed	4500 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	10	Design of the motor type	Compact core type
Rated torque (100 K)	9.5 Nm	Shaft height	80 mm
Rated current	7.8 A	Cooling	Natural cooling
Static torque (60 K)	16.80 Nm	Radial runout tolerance	N
Static torque (100 K)	20.0 Nm	Vibration severity grade	Grade A
Stall current (60 K)	13.0 A	Degree of protection	IP65
Stall current (100 K)	15.6 A	Design acc. to Code I	IM B5 (compatible with 1FT6)
Rotor moment of inertia	0.0045100 kgm ²	Temperature monitoring	Pt1000 temperature sensor
Efficiency	93.0 %	Color of the housing	Standard (pearl dark gray similar to RAL 9023)
Physical constants		Holding brake version	no value
Torque constant	1.28 Nm/A	Shaft end type	Plain shaft
Voltage constant at 20° C	80.0 V/1000*min ⁻¹	Sensor design	Encoder AS24DQI: Absolut encoder Singleturn 24 bit - with signal connection RJ45
Winding resistance at 20° C	0.17 Ω	Electrical connectors	Connector turnable
Rotating field inductance	2.9 mH	Connector size	1.5
Electrical time constant	17.10 ms		
Mechanical time constant	1.40 ms		
Thermal time constant	55 min		
Shaft torsional stiffness	65100 Nm/rad		
Net weight of the motor	20.8 kg		

Data sheet for SIMOTICS S-1FT7

MLFB-Ordering data

1FT7084-1AH71-1BG1



Figure similar

Optimum operating point		Recommended Motor Module	
Optimum speed	4000 rpm	Rated inverter current	18 A
Optimum power	4.8 kW	Maximum inverter current	36 A

Limiting data	
Max. permissible speed (mech.)	8000 rpm
Max. permissible speed (inverter)	7200 rpm
Maximum torque	81.0 Nm
Maximum current	80.0 A