



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : **1PH8166-1FF23-0BA1-Z**
K10+K18+Q12

Client order no. :
 Order no. :
 Offer no. :
 Remarks :

Item no. :
 Consignment no. :
 Project :

Engineering data

		P_N [kW]	M_N [Nm]	I_N [A]	U_N [V]	f_N [Hz]	n_N [rpm]	M_{max} [Nm]	I_{max} [A]	n_{max} [rpm]	M_0 [Nm]	I_0 [A]	η	$\cos \phi$	I_μ [A]
Y	ALM 400V	61.0	333.0	116.0	381	59.5	1,750	730	250.0	6,500	353.0	127	0.940	0.890	35.2
	BLM/SLM 400V	52.0	331.0	116.0	332	51.2	1,500	730	250.0	6,500	353.0	127	0.936	0.880	36.7
	ALM/BLM/SLM 480V	68.0	325.0	116.0	426	67.9	2,000	730	250.0	6,500	353.0	127	0.941	0.890	32.8

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	160
Cooling	Water cooling
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP65
Design acc. to Code I	IM B35 (IM V15, IM V35)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard with fixed bearing
Shaft extension	Plain shaft
Encoder system	Absolut encoder 22 bit Singleturn + 12 bit Multiturn, max. encoder speed = 12000 rpm

Physical constants

Thermal time constant	14 min
Moment of inertia	2,320 kgcm ²
Weight (approx.)	269 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE left
Power connection	top
Signal connection	DE
Terminal box designation	gk873

Cooling data and sound pressure level

Flow rate, min.	15 l/min
Sound pressure level LpA(1m) motor rated load, tolerance + 3dB	69 dB ¹⁾
Pressure drop	0.2 bar
NDE thread connection	0.5 Inches

Cooling water specification

pH value	6 ... 9
Total hardness	1.7 mmol/l
Electrical conductivity	500 µS/cm
Chloride ions	40 mg/l
Sulfate ions	50 mg/l
Nitrate ions	50 mg/l
Dissolved substances	340 mg/l
Maximum particle size	100 µm
Antifreeze/corrosion protection	20 ... 30 %

Special design

K10	Terminal box NDE left
K18	Radial shaft sealing ring DE
Q12	Sealing air connection

¹⁾ at a rated frequency of 4 kHz and a speed range of up to 5000 rpm