

SIMATIC IPC PX-32A 15" ST Singletouch 4 x USB 3.2 (back), Ethernet (10/100/1000) Intel Xeon W-11155MLE (1.8/3.1 GHz, 4C/8T); 16 GB; 1st mass storage: M.2 SSD 256 GB Eco; without 2nd mass storage; Windows 10 IoT Enterprise 2021 LTSC for Celeron processors, W-11155MLE, W-11555MLE; without option 1 with USB flash drive (restore image; D&D) 9-36 V DC industrial power supply (wide range)

Display		
Design of display	15" TFT touch	
Screen diagonal	15.6 in	
Resolution (pixels)		
• Horizontal image resolution	1 366 pixel	
• Vertical image resolution	768 pixel	
Backlighting		
• MTBF backlighting (at 25 °C)	50 000 h	
Control elements		
Input device		
• Mouse, at front	No	
Keyboard fonts		
• Function keys	No	
• alphanumeric keyboard	No	
Touch operation		
• Design as touch screen	Yes	
Installation type/mounting		
central design	Yes	
distributed design	No	
Mounting in portrait format possible	No	
Dimensions		
Width of the housing front	406 mm	
Height of housing front	258 mm	
Mounting cutout, width	388.4 mm	
Mounting cutout, height	240.5 mm	
Overall depth	96 mm	
Weights		
Weight, approx.	6 kg	
Classifications		
	Version	Classification
eClass	14	27-33-02-92
eClass	12	27-33-02-92
eClass	9.1	27-33-02-92
eClass	9	27-33-02-92
eClass	8	27-24-92-03
eClass	7.1	27-24-92-03
eClass	6	27-24-92-03
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
Approvals / Certificates		
General Product Approval		



[Miscellaneous](#)



[BIS CRS](#)

General Product Ap-
proval

Dangerous goods

[KC](#)

[Dangerous goods in-
formation](#)

last modified:

9/9/2024 