

\*\*\* spare part \*\*\* SIMATIC DP, Ethernet/IP head assembly for ET 200S, max. 63 I/O modules incl. motor starter no F modules integrated 2-port switch consisting of:  
\* head module incl. termination module, \* SD card, \* configuration tool (DVD)

General information	
Product type designation	Ethernet/IP interface module
Vendor identification (VendorID)	0008h
Device identifier (DeviceID)	0239h
Supply voltage	
Mains buffering	
<ul style="list-style-type: none"> <li>Mains/voltage failure stored energy time</li> </ul>	20 ms
Input current	
from supply voltage 1L+, max.	250 mA
Power loss	
Power loss, typ.	2.5 W
Address area	
Addressing volume	
<ul style="list-style-type: none"> <li>Inputs</li> <li>Outputs</li> </ul>	256 byte
	256 byte
Interfaces	
Transmission rate, max.	100 Mbit/s
1. Interface	
Autonegotiation	Yes
Interface types	
<ul style="list-style-type: none"> <li>Number of ports</li> </ul>	2
Protocols	
Supports protocol for PROFINET IO	No
Interrupts/diagnostics/status information	
Diagnostics indication LED	
<ul style="list-style-type: none"> <li>LINK LED</li> <li>Monitoring 24 V voltage supply ON (green)</li> </ul>	Yes
	Yes
Potential separation	
between backplane bus and electronics	No
between supply voltage and electronics	No
between Ethernet and electronics	Yes
Isolation	
Isolation tested with	500 V
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes
Dimensions	
Width	60 mm
Height	119.5 mm
Depth	75 mm
Weights	
Weight, approx.	120 g
<b>last modified:</b>	3/12/2024 