

Data sheet for SIMOTICS S-1FT7

Article No. : 1FT7105-5SF71-8BB0



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

Rated speed	3,000 rpm
Number of poles	10
Rated torque (100 K)	48.0 Nm
Rated current	35.00 A
Static torque (60 K)	51.0 Nm
Static torque (100 K)	65.0 Nm
Stall current (60 K)	36.00 A
Stall current (100 K)	45.00 A
Rotor moment of inertia	206.00 kgcm ²
Efficiency	93.0 %

Physical constants

Torque constant	1.43 Nm/A
Voltage constant at 20° C	91.0 V/1000*min ⁻¹
Winding resistance at 20° C	0.05 Ω
Rotary field inductance	1.3 mH
Electrical time constant	25.00 ms
Mechanical time constant	1.30 ms
Thermal time constant	50 min
Shaft torsional stiffness	107,000 Nm/rad
Net weight of the motor	56.0 kg

Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	100
Cooling	Forced ventilation
Radial runout tolerance	0.050 mm
Concentricity tolerance	0.100 mm
Axial runout tolerance	0.100 mm
Vibration severity grade	Grade A
Degree of protection	IP64
Design acc. to Code I	IM B5 (compatible with 1FT6)
Temperature monitoring	Pt1000 temperature sensor
Shaft end type	Fitted key and keyway
Sensor design	Encoder AS24DQI: Absolut encoder Singleturn 24 bit - with signal connection RJ45
Electrical connection	Terminal box axial DE

Optimum operating point

Optimum speed	3,000 rpm
Optimum power	15.1 kW

Limiting data

Max. permissible speed (mech.)	6,000 rpm
Max. permissible speed (inverter)	6,000 rpm
Maximum torque	200.0 Nm
Maximum current	158.00 A

Recommended Motor Module

Rated inverter current	45.00 A
Maximum inverter current	85.00 A
Maximum torque	120.0 Nm

Holding brake

Holding brake version	Permanent-magnet brake
Holding torque	85.0 Nm
Braking torque	35.0 Nm
Power supply voltage	DC 24 V
Coil current	1.60 A
Permissible brake work	5,300 J
Opening time	250 ms
Closing time	70 ms