

## Data sheet for SIMOTICS S-1FT7

Article No. : 1FT7134-5AC71-1CA0



Figure similar

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

|                         |                          |
|-------------------------|--------------------------|
| Rated speed             | 2,000 rpm                |
| Number of poles         | 8                        |
| Rated torque (100 K)    | 66.0 Nm                  |
| Rated current           | 21.00 A                  |
| Static torque (60 K)    | 100.0 Nm                 |
| Static torque (100 K)   | 118.0 Nm                 |
| Stall current (60 K)    | 30.50 A                  |
| Stall current (100 K)   | 36.00 A                  |
| Rotor moment of inertia | 604.00 kgcm <sup>2</sup> |
| Efficiency              | 95.0 %                   |

### Physical constants

|                             |                                |
|-----------------------------|--------------------------------|
| Torque constant             | 3.27 Nm/A                      |
| Voltage constant at 20° C   | 215.0 V/1000*min <sup>-1</sup> |
| Winding resistance at 20° C | 0.10 Ω                         |
| Rotary field inductance     | 3.6 mH                         |
| Electrical time constant    | 36.00 ms                       |
| Mechanical time constant    | 1.70 ms                        |
| Thermal time constant       | 80 min                         |
| Shaft torsional stiffness   | 323,000 Nm/rad                 |
| Net weight of the motor     | 92.0 kg                        |

### Mechanical data

|                          |  |
|--------------------------|--|
| Motor type               | Permanent-magnet synchronous motor   |
| Motor type               | Compact  |
| Shaft height             | 132  |
| Cooling                  | Natural cooling  |
| Radial runout tolerance  | 0.050 mm   |
| Concentricity tolerance  | 0.125 mm   |
| Axial runout tolerance   | 0.125 mm   |
| Vibration severity grade | Grade A  |
| Degree of protection     | IP64   |
| Design acc. to Code I    | IM B5 (compatible with 1FT6)   |
| Temperature monitoring   | Pt1000 temperature sensor  |
| Color of the housing     | Standard (pearl dark gray similar to RAL 9023)   |
| Shaft end type           | Fitted key and keyway  |
| Sensor design            | Encoder AM24DQI: Absolute encoder 24 bit (resolution 16777216, encoder-internal 2048 S/R) + 12 bit Multiturn (traversing range 4096 revolutions) - with signal connection RJ45 |
| Electrical connection    | Connector turnable   |
| Connector size           | 1.5  |

### Optimum operating point

|               |           |
|---------------|-----------|
| Optimum speed | 1,880 rpm |
| Optimum power | 14.0 kW   |

### Limiting data

|                                   |           |
|-----------------------------------|-----------|
| Max. permissible speed (mech.)    | 3,600 rpm |
| Max. permissible speed (inverter) | 2,650 rpm |
| Maximum torque                    | 390.0 Nm  |
| Maximum current                   | 146.00 A  |

### Recommended Motor Module

|                          |          |
|--------------------------|----------|
| Rated inverter current   | 45.00 A  |
| Maximum inverter current | 85.00 A  |
| Maximum torque           | 260.0 Nm |