



Figure similar

### MLFB-Ordering data

6SL3121-1TE28-5AA3

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		Ambient conditions	
DC link voltage	DC 510 ... 720 V	Installation altitude (without derating)	1000 m (3281 ft)
Electronics power supply	DC 24 V -15 % / +20 %	Cooling <sup>8)</sup>	External air cooling
Current demand, max.	1.50 A	Cooling air requirement	0.044 m <sup>3</sup> /s
DC-link current I <sub>d</sub>	102.0 A	Ambient temperature	
Output current		During operation	0 ... 40 °C (32 ... 104 °F)
Rated value I <sub>N</sub>	85.0 A	Connections	
Base load current I <sub>H</sub>	68.0 A	Motor end	
For S6 duty (40%) I <sub>S6</sub>	110.0 A	Version	M8 bolt (X1)
I <sub>max</sub>	141.0 A	Conductor cross-section	3 ... 95 mm <sup>2</sup> (14 ... -2 AWG)
Type rating <sup>2)</sup>		PE connection	M6 screw
Based on I <sub>N</sub>	46.0 kW	Max. motor cable length	
Based on I <sub>H</sub>	37.0 kW	Shielded	100 m (328 ft)
Rated pulse frequency	4.00 kHz	Unshielded	150 m (492 ft)
Current carrying capacity		Standards	
DC link busbars	200 A	Compliance with standards	CE, cULus
24 V busbars	20 A	Safety Integrated	SIL 2 acc. to IEC 61508, PL d acc. to EN ISO 13849-1, Category 3 acc. to EN ISO 13849-1
DC link capacitance	1880 μF		

MLFB-Ordering data

6SL3121-1TE28-5AA3



Figure similar

### Mechanical data

#### Line side

Width	200.00 mm (7.87 in)
Height	380.00 mm (14.96 in)
Depth	226.00 mm (8.90 in)
Degree of protection	IP20 / UL open type
Type of construction	Booksize
Net weight	17.2 kg (37.92 lb)

### General tech. specifications

Sound pressure level (1m)	60.0 dB
Power loss, max. <sup>9)</sup>	0.59 kW

2) Rated output of a typical standard asynchronous motor at 400 V 3 AC

8) Power units with intensified air cooling thanks to integrated fan

9) Power loss of the Motor Module with rated power including losses of the 24 V DC electronics power supply