

RUGGEDCOM RX1500PN LM CG01 Line Module 2 x 10/100/1000 TX RJ45  
Conformal Coating

suitability for operation	RX1500, RX1501, RX1510, RX1511, RX1512
<b>interfaces</b>	
number of electrical/optical connections / for network components or terminal equipment / maximum	2
number of electrical connections <ul style="list-style-type: none"> <li>for network components or terminal equipment / maximum</li> </ul>	2
<b>ambient conditions</b>	
ambient temperature <ul style="list-style-type: none"> <li>during operation</li> <li>during storage</li> <li>during transport</li> <li>note</li> </ul>	-40 ... +85 °C -40 ... +85 °C -40 ... +85 °C A maximum operating temperature of +85 °C is permissible for a duration of 16 hours
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP40
<b>design, dimensions and weights</b>	
design	Media module
width	20 mm
height	115 mm
depth	180 mm
net weight	0.35 kg
product feature / conformal coating	Yes
fastening method <ul style="list-style-type: none"> <li>installation in media module slot</li> </ul>	screwed Yes
<b>standards, specifications, approvals</b>	
standard <ul style="list-style-type: none"> <li>for EMC</li> <li>for safety / from CSA and UL</li> <li>for hazardous zone / from CSA and UL</li> <li>for emitted interference</li> <li>for interference immunity</li> </ul>	FCC Part 15 (Class A), EN55022 (CISPR22 Class A) UL 60950-1, CSA C22.2 No. 60950-7 Hazardous Locations: Class 1 Division 2 EN 61000-6-4 (Class A) EN 61000-6-2
certificate of suitability <ul style="list-style-type: none"> <li>CE marking</li> <li>C-Tick</li> <li>KC approval</li> <li>E1 approval</li> <li>railway application in accordance with EN 50155</li> <li>railway application in accordance with EN 50124-1</li> <li>IEC 61850-3</li> </ul>	EN 61000-6-2, EN 61000-6-10 Yes No No No Yes Yes Yes
<b>further information / internet links</b>	
internet link <ul style="list-style-type: none"> <li>to website: Industry Mall/RUGGEDCOM selector</li> <li>to website: Siemens RUGGEDCOM</li> <li>to website: Industrial communication</li> <li>to website: Industry Mall</li> <li>to website: Information and Download Center</li> <li>to website: Selection guide for cables and connectors</li> <li>to website: Image database</li> <li>to website: CAx-Download-Manager</li> <li>to website: Industry Online Support</li> </ul>	<a href="http://ruggedcom-selector.automation.siemens.com">http://ruggedcom-selector.automation.siemens.com</a> <a href="http://siemens.com/ruggedcom">http://siemens.com/ruggedcom</a> <a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a> <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a> <a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a> <a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a> <a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a> <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a> <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>

---

last modified:

10/20/2023 