

Data sheet for SIMOTICS S-1FT7



Figure similar

MLFB-Ordering data

1FT7044-5AK70-1CH3

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data		Mechanical data	
Rated speed	6000 rpm	Motor type	Permanent-magnet synchronous motor
Number of poles	6	Design of the motor type	Compact
Rated torque (100 K)	2.0 Nm	Shaft height	48 mm
Rated current	2.5 A	Cooling	Natural cooling
Static torque (60 K)	4.40 Nm	Radial runout tolerance	N
Static torque (100 K)	5.0 Nm	Vibration severity grade	Grade R
Stall current (60 K)	4.9 A	Degree of protection	IP64
Stall current (100 K)	5.7 A	Design acc. to Code I	IM B5 (new flange design)
Rotor moment of inertia	0.0006300 kgm ²	Temperature monitoring	Pt1000 temperature sensor
Efficiency	91.0 %	Color of the housing	
Physical constants		Holding brake version	Permanent-magnet brake
Torque constant	0.89 Nm/A	Shaft end type	Plain shaft
Voltage constant at 20° C	56.5 V/1000*min ⁻¹	Sensor design	Encoder AM24DQI: Absolute encoder 24 bit (resolution 16777216, encoder-internal 2048 S/R) + 12 bit Multiturn (traversing range 4096 revolutions) - with signal connection RJ45
Winding resistance at 20° C	0.61 Ω	Electrical connectors	Connector turnable
Rotating field inductance	4.2 mH	Connector size	1
Electrical time constant	7.00 ms		
Mechanical time constant	1.30 ms		
Thermal time constant	35 min		
Shaft torsional stiffness	9500 Nm/rad		
Net weight of the motor	8.1 kg		

Data sheet for SIMOTICS S-1FT7

MLFB-Ordering data

1FT7044-5AK70-1CH3



Figure similar

Optimum operating point		Recommended Motor Module	
Optimum speed	4500 rpm	Rated inverter current	9 A
Optimum power	1.4 kW	Maximum inverter current	27 A
Limiting data		Maximum torque	21.90 Nm
Max. permissible speed (mech.)	9000 rpm		
Max. permissible speed (inverter)	9000 rpm		
Maximum torque	23.0 Nm		
Maximum current	30.0 A		