



MLFB-Ordering data: **1LE1023-0DA32-2AA4**

Motor type: **1AV3083A**

Client order no.:

Item no.:

Order no.:

Consignment no.:

Offer no.:

Project:

Remarks:

U [V]	Δ/Y	f [Hz]	P		I [A]	n [1/min]	M [Nm]	NOM. EFF at ... load [%]			Power factor at ... load			$I_A/I_N$   $I/I_N$	$M_A/M_N$   $T/T_N$	$M_K/M_N$   $T_B/T_N$	IE-CL
			[kW]	[hp]				4/4	3/4	2/4	4/4	3/4	2/4				
230	Δ	50	1.10	- / -	3.95	2885	3.6	82.7	83.9	83.1	0.85	0.80	0.69	7.1	3.0	3.3	IE3
400	Y	50	1.10	- / -	2.25	2885	3.6	82.7	83.9	83.1	0.85	0.80	0.69	7.1	3.0	3.3	IE3
460	Y	60	1.27	- / -	2.25	3480	3.5	84.0	84.6	83.4	0.85	0.80	0.71	7.4	2.8	3.4	IE3
460	Y	60	1.10	1.50	1.98	3500	3.0	84.0	84.0	82.0	0.83	0.77	0.67	8.4	3.3	4.0	MG1
IM B3 / IM 1001			FS 80 M		12 kg	IP55	CC032A	IEC/EN 60034		IEC, EN, UL, CSA, NEMA MG1-12-12			kVA Code: M				

Mechanical data			Terminal box	
Sound pressure level 50Hz/60Hz (load)	60 dB(A) <sup>1)</sup>	64 dB(A) <sup>1)</sup>	Terminal box position	top
Moment of inertia	0.0013 kg m <sup>2</sup>		Material of terminal box	Aluminium
Bearing DE   NDE	6004 2Z C3	6004 2Z C3	Type of terminal box	TB1 E10
Bearing lifetime	40000 h		Contact screw thread	M4
Lubricants	Unirex N3		Max. cross-sectional area	1.5 mm <sup>2</sup>
Regreasing device	No		Cable diameter from ... to ...	9.0 mm - 17.0 mm
Grease nipple	- / -		Cable entry	1xM25x1,5
Type of bearing	Preloaded bearing DE		Cable gland	1 plug
Condensate drainage holes	No			
External earthing terminal				
Vibration severity grade	A		Special design (0)	
Insulation	155(F) to 130(B)			
Duty type	S1			
Direction of rotation	bidirectional			
Frame material	aluminum			
Data of anti condensation heating	-/-			
Coating (paint finish)	Standard paint finish C2			
Color, paint shade	RAL7030			
Motor protection	(A) without (Standard)			
Method of cooling	IC411 - self ventilated, surface cooled			

Environmental conditions	
Ambient temperature	-20 °C - +40 °C
Altitude above sea level	1000 m

Notes	
$I_A/I_N$ = locked rotor current / current	$M_K/M_N$ = break down torque / nominal torque
$M_A/M_N$ = locked rotor torque / torque	1) at rated power