

Article No. : 1FK7103-5AF71-1GG5

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

Figure similar

### Engineering data

Rated speed (100 K)	3,000 rpm
Number of poles	8
Rated torque (100 K)	14.0 Nm
Rated current	12.0 A
Static torque (60 K)	30.00 Nm
Static torque (100 K)	36.00 Nm
Stall current (60 K)	22.80 A
Stall current (100 K)	27.50 A
Moment of inertia	105.000 kgcm <sup>2</sup>
Efficiency	93.0 %

### Physical constants

Torque constant	1.35 Nm/A
Voltage constant at 20° C	86.0 V/1000*min <sup>-1</sup>
Winding resistance at 20° C	0.09 Ω
Rotating field inductance	2.0 mH
Electrical time constant	22.20 ms
Mechanical time constant	1.55 ms
Thermal time constant	65 min
Shaft torsional stiffness	149,000 Nm/rad
Net weight of the motor	29.0 kg

### Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	100
Cooling	Natural cooling
Radial runout tolerance	0.050 mm
Concentricity tolerance	0.10 mm
Axial runout tolerance	0.10 mm
Vibration severity grade	Grade A
Connector size	1.5
Degree of protection	IP65 and DE flange IP67
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	Standard (Anthracite RAL 7016)
Holding brake	without holding brake
Shaft end	Plain shaft
Encoder system	Encoder AM32S/R: absolute encoder 32 S/R, 4096 revolutions multi-turn, with EnDat interface

### Optimum operating point

Optimum speed	2,500 rpm
Optimum power	5.4 kW

### Limiting data

Max. permissible speed (mech.)	5,000 rpm
Max. permissible speed (inverter)	6,700 rpm
Maximum torque	108.0 Nm
Maximum current	84.0 A

### Recommended Motor Module

Rated inverter current	30 A
Maximum inverter current	56 A
Maximum torque	73.00 Nm